



Data sheet Polytronik® Toroidal transformer

Part no.:	RSO 825039
Description:	RKT200VA/ 2x115V/ 2x15V 2x6.67A
Safety isolating transformer according to:	EN 61558-2-6 / VDE 0570
Power [VA]:	200
Input voltage [AC]:	2 x 115 V +-10%
Output voltage [AC]:	2 x 15.00 V
Output current [AC]:	2 x 6.67 A
Frequency [Hz]:	50/60
Dielectric strength PRI - SEC [AC]:	4400 V
Efficiency [%]:	91
Power loss at no-load [W]:	1.91
Maximum ambient temperature t_a [°C]:	60
Temperature class:	B (130°C)
Temperature switch:	120°C (automatically resetting)



Schematic:



possible connection: parallel connection **115V** = connect blue with blue and brown with brown
PRI 1 und PRI 2 series connection **230V** = connect brown with blue

possible connection: parallel connection **15.0V / 13.34A** = connect black with violet and red with white
SEC 1 und SEC 2 series connection **30.0V / 6.67A** = connect red with violet

Approval marks:	CE; ENEC; UL508 (E182061)		
Connections:	primary and secondary strands 200mm long, ends assembled with ferrules		
Model:	toroidal transformer pottet on mounting disc with through-hole 8.1 mm		
Appliance class:	prepared for class II		
Protection class:	IP 00		
Recommended fuse ratings:	primary	3.15 AT / 1.60 AT (115V / 230V)	(IEC60127-2-5)
	secondary 1	8.00 AT	(IEC60127-2-3)
	secondary 2	8.00 AT	(IEC60127-2-3)
Dimensions:	diameter approx. =	115 mm	
	height approx. =	62 mm	
Weight:	approx. 2.54 kg		