

# SAFETY DATA SHEET

## CONTACT CLEANER LUBRICANT Aerosol

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** CONTACT CLEANER LUBRICANT Aerosol  
**Product number** EML-a, EEML200F, EEML400D, ZE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Manufacture of electrical equipment  
**Uses advised against** At this moment in time we do not have information on use restrictions. They will be included in this safety data sheet when available

#### 1.3. Details of the supplier of the safety data sheet

**Supplier**  
**Manufacturer** ELECTROLUBE. A division of HK WENTWORTH LTD  
 ASHBY PARK, COALFIELD WAY,  
 ASHBY DE LA ZOUCH, LEICESTERSHIRE LE65 1JR  
 UNITED KINGDOM  
  
 +44 (0)1530 419600  
 +44 (0)1530 416640  
 info@hkw.co.uk

#### 1.4. Emergency telephone number

**Emergency telephone** +44 (0)1530 419600 between 8.30am - 5.00pm Mon – Fri

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

**Physical hazards**  
 Aerosol 1 - H222, H229

**Health hazards**  
 STOT SE 3 - H336

**Environmental hazards**  
 Aquatic Chronic 2 - H411

##### Classification (67/548/EEC or 1999/45/EC)

F+;R12. N;R51/53. R66,R67.

##### Physicochemical

Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

#### 2.2. Label elements

##### Pictogram



**Signal word**

Danger

**Hazard statements**

**CONTACT CLEANER LUBRICANT Aerosol**

H229 Pressurised container: may burst if heated  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.  
 H222 Extremely flammable aerosol.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P271 Use only outdoors or in a well-ventilated area.

**Supplemental label information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Supplementary precautionary statements**

P261 Avoid breathing vapour/spray.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**2.3. Other hazards**

This substance is not classified as PBT or vPvB according to current EU criteria.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

|  |  |
|--|--|
| <b>PENTANE</b> <span style="float: right;"><b>60-100%</b></span>   |  |
| <b>CAS number:</b> 109-66-0 <b>EC number:</b> 203-692-4 <b>REACH registration number:</b> 01-2119459286-30         |  |
| <b>Classification</b><br>Flam. Liq. 2 - H225<br>Asp. Tox. 1 - H304<br>STOT SE 3 - H336<br>Aquatic Chronic 2 - H411 | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>F+;R12 Xn;R65 R66 R67 N;R51/53 |
| <b>PROPAN-2-OL</b> <span style="float: right;"><b>1-5%</b></span>  |  |
| <b>CAS number:</b> 67-63-0 <b>EC number:</b> 200-661-7 <b>REACH registration number:</b> 01-2119457558-25-XXXX     |  |
| <b>Classification</b><br>Flam. Liq. 2 - H225<br>Eye Irrit. 2 - H319<br>STOT SE 3 - H336<br>STOT SE 3 - H336        | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>F;R11 Xi;R36 R67               |
| <b>DIPHENYLAMINE</b> <span style="float: right;"><b>&lt;1%</b></span>  |  |
| <b>CAS number:</b> 122-39-4 <b>EC number:</b> 204-539-4<br><b>M factor (Acute) = 1 M factor (Chronic) = 1</b>      |  |
| <b>Classification</b><br>Acute Tox. 3 - H301<br>Acute Tox. 3 - H311<br>Acute Tox. 3 - H331<br>STOT RE 2 - H373     | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>T;R23/24/25 R33 N;R50/53       |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments**

No classified ingredients, or those having occupational exposure limits, present above the levels of disclosure.

## CONTACT CLEANER LUBRICANT Aerosol

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### **Inhalation**

Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately. Get medical attention.

##### **Ingestion**

Rinse mouth thoroughly with water.

##### **Skin contact**

Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

##### **Eye contact**

Remove any contact lenses and open eyelids wide apart. Rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

##### **Notes for the doctor**

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

##### **Specific hazards**

The product is flammable. Heating may generate flammable vapours. Containers can burst violently or explode when heated, due to excessive pressure build-up. Containers can burst violently or explode when heated, due to excessive pressure build-up.

##### **Hazardous combustion products**

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### 5.3. Advice for firefighters

##### **Protective actions during firefighting**

Move containers from fire area if it can be done without risk.

##### **Special protective equipment for firefighters**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### **Personal precautions**

Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Nettoyer les déversements immédiatement en respectant les mesures de précaution de la rubrique Équipement de protection.

#### 6.2. Environmental precautions

##### **Environmental precautions**

Do not discharge into drains or watercourses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

##### **Methods for cleaning up**

Absorb in vermiculite, dry sand or earth and place into containers. Provide adequate ventilation.

#### 6.4. Reference to other sections

##### **Reference to other sections**

Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health

## CONTACT CLEANER LUBRICANT Aerosol

hazards. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

---

### SECTION 7: Handling and storage

---

#### 7.1. Precautions for safe handling

##### **Usage precautions**

Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### **Storage precautions**

Store at moderate temperatures in dry, well ventilated area.

#### 7.3. Specific end use(s)

##### **Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

---

### SECTION 8: Exposure Controls/personal protection

---

#### 8.1. Control parameters

##### Occupational exposure limits

##### **PENTANE**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1800 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

##### **PROPAN-2-OL**

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m<sup>3</sup>

##### **DIPHENYLAMINE**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 20 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

##### **Ingredient comments**

Australian exposure limits are: LT= ES-TWA and ST= ES STEL

**CONTACT CLEANER LUBRICANT Aerosol****PENTANE (CAS: 109-66-0)**

|      |   |
|------|---|
| DNEL | Industry - Dermal; Long term systemic effects: 432 mg/kg/day<br>Industry - Inhalation; Long term systemic effects: 3000 mg/m3<br>Consumer - Oral; Long term systemic effects: 214 mg/kg/day<br>Consumer - Dermal; Long term systemic effects: 214 mg/kg/day<br>Consumer - Inhalation; Long term systemic effects: 643 mg/m3 |
| PNEC | - water; 0.23 mg/l<br>- Sediment; 1.2 mg/kg<br>- Soil; 0.55 mg/kg<br>- STP; 3.6 mg/l  |

**PROPAN-2-OL (CAS: 67-63-0)**

|      |  |
|------|--|
| DNEL | Industry - Dermal; : 888 mg/kg/day<br>Industry - Inhalation; : 500 mg/m3<br>Consumer - Dermal; : 319 mg/kg/day<br>Consumer - Inhalation; : 89 mg/m3<br>Consumer - Oral; : 26 mg/kg/day |
| PNEC | - Fresh water; 140.9 mg/l<br>- Marine water; 140.9 mg/l<br>- Sediment; 552 mg/kg<br>- Soil; 28 mg/kg   |

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

**Eye/face protection**

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. EN166

**Hand protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). Gloves should conform to EN374

**Other skin and body protection**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**Hygiene measures**

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.

**Respiratory protection**

If ventilation is inadequate, suitable respiratory protection must be worn. It is recommended to use respiratory equipment with combination filter, type A2/P2. EN14387

**SECTION 9: Physical and Chemical Properties****9.1. Information on basic physical and chemical properties****Appearance**

Aerosol. Liquid.

**Colour**

Colourless.

**Odour**

Characteristic.

**CONTACT CLEANER LUBRICANT Aerosol****Melting point**

-130°C/-202°F

**Initial boiling point and range**

36°C/96.8°F @

**Flash point**

-48°C/-54.4°F CC (Closed cup).

**Upper/lower flammability or explosive limits**

: 1.4

**Vapour pressure**

5.33 kPa @ 20°C/68°F

**Relative density**

0.650 @ 20°C/68°F

**Bulk density**

650 kg/m<sup>3</sup>

**Solubility(ies)**

Immiscible with water.

**Auto-ignition temperature**

309°C/588.2°F

**Comments**

Information given is applicable to the major ingredient.

**9.2. Other information****SECTION 10: Stability and reactivity****10.1. Reactivity**

There are no known reactivity hazards associated with this product.

**10.2. Chemical stability****Stability**

Stable at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Not available. Will not polymerise.

**10.4. Conditions to avoid**

Avoid heat, flames and other sources of ignition.

**10.5. Incompatible materials****Materials to avoid**

Strong alkalis. Strong acids.

**10.6. Hazardous decomposition products**

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicological effects**

No information available.

**Other health effects**

There is no evidence that the product can cause cancer.

**Inhalation**

May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Gas or vapour in high

### **CONTACT CLEANER LUBRICANT Aerosol**

concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

#### **Skin contact**

Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin. Prolonged or repeated exposure may cause severe irritation.

#### **Eye contact**

Irritating to eyes.

#### **Route of entry**

Inhalation

#### Toxicological information on ingredients.

#### PENTANE

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg)

2,000

**CONTACT CLEANER LUBRICANT Aerosol****PROPAN-2-OL****Acute toxicity - oral****Acute toxicity oral (LD<sub>50</sub> mg/kg)**

4,700.0

**Species**

Rat

**ATE oral (mg/kg)**

4,700.0

**Acute toxicity - dermal****Acute toxicity dermal (LD<sub>50</sub> mg/kg)**

12800

**Species**

Rabbit

**Acute toxicity - inhalation****Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)**

46.5

**Species**

Rat

**ATE inhalation (vapours mg/l)**

46.5

**Inhalation**

Vapours may cause headache, fatigue, dizziness and nausea.

**Eye contact**

Irritating to eyes.

**Acute and chronic health hazards**

Irritation of eyes and mucous membranes. Narcotic effect. Central nervous system depression.

**Route of entry**

Skin and/or eye contact Skin absorption Ingestion

**Target organs**

Central nervous system Eyes Skin Respiratory system, lungs

**Medical symptoms**

Irritation of eyes and mucous membranes. Dilated pupils. Rhinitis (inflammation of the nasal mucous membranes). General respiratory distress, unproductive cough. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

**Benzamine, N phenyl, reaction product with 2,4,4 trimethylpentene****Acute toxicity - oral****Acute toxicity oral (LD<sub>50</sub> mg/kg)**

2,000

**Species**

Rat

**Acute toxicity - dermal****Acute toxicity dermal (LD<sub>50</sub> mg/kg)**

2000

**Species**

Rat



## CONTACT CLEANER LUBRICANT Aerosol

### SECTION 12: Ecological Information

#### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

#### 12.1. Toxicity

##### Ecological information on ingredients.

##### PROPAN-2-OL

##### Acute toxicity - fish

LC50, 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)

##### Acute toxicity - aquatic invertebrates

EC50, 48 hours: 13299 mg/l, Daphnia magna

##### Acute toxicity - aquatic plants

EC50, 72 hours: > 1.000 mg/l, Scenedesmus subspicatus

##### Acute toxicity - microorganisms

EC50, >: > 1.000 mg/l, Activated sludge

##### Benzamine, N phenyl, reaction product with 2,4,4 trimethylpentene

##### Acute toxicity - fish

LC50, 96 hours: > 71 mg/l, Brachydanio rerio (Zebra Fish) LC50, 96 hours: mg/l, Fish

##### Acute toxicity - aquatic invertebrates

EC50, 48 hours: 51 mg/l, Daphnia magna EC50, 48 hours: mg/l, Daphnia magna

##### Acute toxicity - aquatic plants

EC50, 72 hours: > 100 mg/l, Scenedesmus subspicatus

#### 12.2. Persistence and degradability

##### Persistence and degradability

There are no data on the degradability of this product.

##### Ecological information on ingredients.

##### PROPAN-2-OL

##### Persistence and degradability

The product is readily biodegradable.

##### Benzamine, N phenyl, reaction product with 2,4,4 trimethylpentene

##### Persistence and degradability

The product is not biodegradable.

#### 12.3. Bioaccumulative potential

No data available on bioaccumulation.

##### Ecological information on ingredients.

##### PROPAN-2-OL

The product does not contain any substances expected to be bioaccumulating.

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

##### Ecological information on ingredients.

##### PROPAN-2-OL

This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

## CONTACT CLEANER LUBRICANT Aerosol

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal methods

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1litre packed in cartons of less than 30kg gross weight to be exempt from control providing they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed must show the following.

#### 14.1. UN number

|                  |      |
|------------------|------|
| UN No. (ADR/RID) | 1950 |
| UN No. (IMDG)    | 1950 |
| UN No. (ICAO)    | 1950 |

#### 14.2. UN proper shipping name

|                                |                    |
|--------------------------------|--------------------|
| Proper shipping name (ADR/RID) | AEROSOLS (PENTANE) |
| Proper shipping name (IMDG)    | AEROSOLS (PENTANE) |
| Proper shipping name (ICAO)    | AEROSOLS (PENTANE) |
| Proper shipping name (ADN)     | AEROSOLS (PENTANE) |
| Proper Shipping Name (DOT)     |                    |

#### 14.3. Transport hazard class(es)

|                         |     |
|-------------------------|-----|
| ADR/RID class           | 2.1 |
| ADR/RID subsidiary risk |     |
| ADR/RID label           | 2.1 |
| IMDG class              | 2.1 |
| IMDG subsidiary risk    |     |
| ICAO class/division     | 2.1 |
| ICAO subsidiary risk    |     |

##### Transport labels



#### 14.4. Packing group

Not applicable.

|                       |  |
|-----------------------|--|
| ADR/RID packing group |  |
| IMDG packing group    |  |
| ICAO packing group    |  |

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

**CONTACT CLEANER LUBRICANT Aerosol**

Yes.

**14.6. Special precautions for user**

EmS F-D, S-U

Emergency Action Code

Hazard Identification Number  
(ADR/RID)

Tunnel restriction code (D)

Markings

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Control of Substances Hazardous to Health Regulations 2002 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

**EU legislation**

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance****Authorisations (Title VII Regulation 1907/2006)**

No specific authorisations are known for this product.

**Restrictions (Title VIII Regulation 1907/2006)**

No specific restrictions on use are known for this product.

**Water hazard classification**

WGK 2

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

**SECTION 16: Other information**

Issued by Grace Claypole

Revision date 05/03/2015

Revision 8

SDS number 11552

Risk phrases in full

### **CONTACT CLEANER LUBRICANT Aerosol**

R11 Highly flammable.

R12 Extremely flammable.

R36 Irritating to eyes.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

#### **Hazard statements in full**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

#### **Disclaimer**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.