

## Connector - C-SCF 1,5/4,8X0,8 - 3240155

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Slip-on sleeve, non-insulated, 0.75 - 1.5 mm<sup>2</sup>, 4.8 x 0.8

The figure shows a version of the article

### Product Features

- They round out the product range in terms of connectors
- The uninsulated slip-on sleeves and flat plugs are made from electrolytically tin-plated brass

### Key commercial data

<b>package_quantity</b>	100
<b>GTIN</b>	4046356453721

### Technical data

#### Dimensions

<b>Length (b)</b>	15.6 mm
<b>Width (a)</b>	4.8 mm
<b>Material thickness (g)</b>	0.4 mm

#### Ambient conditions

<b>Ambient temperature (operation)</b>	110 °C
--	--------

#### General

<b>Color</b>	silver
<b>Stripping length</b>	7 mm
<b>Components</b>	Halogen-free
<b>Material</b>	Brass

### classifications

#### eCl@ss

<b>eCl@ss 4.0</b>	27060701
<b>eCl@ss 4.1</b>	27060701
<b>eCl@ss 5.0</b>	27400201
<b>eCl@ss 5.1</b>	27400201
<b>eCl@ss 6.0</b>	27400201

## Connector - C-SCF 1,5/4,8X0,8 - 3240155

### classifications

#### eCl@ss

eCl@ss 7.0	27400201
eCl@ss 8.0	27400201

#### ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC001052
ETIM 5.0	EC001052

#### UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

### Drawings

# Connector - C-SCF 1,5/4,8X0,8 - 3240155

Dimensioned drawing

