

## Electronic housing - ME MAX 12,5 3-3 TBUS KMGY - 2279020

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Electronic housing, design width 12.5 mm, 3 connection levels per side, for DIN rail bus connectors

#### **Product Features**

- ☑ DIN rail bus connector as an option
- Plug-in connection with screw, spring-cage or fast connection technology

- The fitted cover is easy to adapt and print

- Fixed or plug-in connection technology can be combined on up to three connection levels, with different pitches

## Key commercial data

package_quantity	10
GTIN	4046356180580

#### Technical data

#### General

Housing type	Complete housing
Housing material	Polyamide
Color	light gray

#### **Dimensions**

Length	99 mm
Constructional height	114.5 mm
Width	12.5 mm

#### Technical data

Inflammability class according to UL 94	V0
Power dissipation at 20°C in the horizontal mounting position	4.4 W 8.4 W



# Electronic housing - ME MAX 12,5 3-3 TBUS KMGY - 2279020

## classifications

## eCl@ss

eCI@ss 4.0	27180401
eCl@ss 4.1	27180401
eCI@ss 5.0	27180506
eCl@ss 5.1	27180506
eCI@ss 6.0	27180802
eCI@ss 7.0	27182702
eCl@ss 8.0	27182702

### **ETIM**

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031

### **UNSPSC**

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## approvals

UL Recognized /

### Approval details

UL Recognized **\$\)** 

## Drawings

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com