

# Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



PLC sensor interface, consisting of PLC-BSC...SEN basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on NS 35/7,5 DIN rails, input: 24 V DC, output: 3 - 48 V DC/100 mA

## Product Features

- ✔ No need for additional modular terminal blocks
- ✔ Efficient connection to system cabling using V8 adapter
- ✔ Time savings of up to 60%
- ✔ Relay modules with safe isolation according to DIN EN 50178 between coil and contact
- ✔ Space savings of up to 80%
- ✔ Sensor connected directly to relay module
- ✔ Functional plug-in bridges



## Key commercial data

package_quantity	10
GTIN	4017918130596

## Technical data

Note:

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

### Dimensions

Width	6.2 mm
Height	80 mm
Depth	94 mm

### Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

### Input data

Nominal input voltage $U_N$	24 V DC
Input voltage range in reference to $U_N$	0.8 ... 1.2

# Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

## Technical data

### Input data

Switching threshold "0" signal in reference to U <sub>N</sub>	≤ 0.4
Switching threshold "1" signal in reference to U <sub>N</sub>	≥ 0.8
Typical input current at U <sub>N</sub>	8.5 mA
Typical response time	20 μs (at U <sub>N</sub> )
Typical turn-off time	300 μs (at U <sub>N</sub> )
Operating voltage display	Yellow LED
Type of protection	Protection against polarity reversal
Type of protection	Free-wheeling diode
Protective circuit/component	Polarity protection diode
Protective circuit/component	Damping diode
Transmission frequency	300 Hz

### Output data

Output voltage range	3 V DC ... 48 V DC
Limiting continuous current	100 mA
Voltage drop at max. limiting continuous current	≤ 1 V
Output circuit	2-wire, floating
Type of protection	Protection against polarity reversal
Type of protection	Surge protection
Protective circuit/component	Polarity protection diode

### Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid min.	0.14 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.14 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	14

### General

Test voltage input/output	2.5 kV (50 Hz, 1 min.)
Mounting position	Any
Assembly instructions	In rows with zero spacing
Operating mode	100% operating factor
Inflammability class according to UL 94	V0
Name	Standards/regulations
Standards/regulations	IEC 60664
Standards/regulations	EN 50178

# Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

## Technical data

### General

<b>Standards/regulations</b>	IEC 62103
<b>Rated surge voltage / insulation</b>	Basic insulation
<b>Pollution degree</b>	2
<b>Surge voltage category</b>	III

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27371102
<b>eCl@ss 4.1</b>	27371102
<b>eCl@ss 5.0</b>	27371001
<b>eCl@ss 5.1</b>	27371001
<b>eCl@ss 6.0</b>	27371001
<b>eCl@ss 7.0</b>	27371001
<b>eCl@ss 8.0</b>	27371001

### ETIM

<b>ETIM 2.0</b>	EC001504
<b>ETIM 3.0</b>	EC001504
<b>ETIM 4.0</b>	EC001504
<b>ETIM 5.0</b>	EC001504

### UNSPSC

<b>UNSPSC 6.01</b>	30211916
<b>UNSPSC 7.0901</b>	39121542
<b>UNSPSC 11</b>	39121542
<b>UNSPSC 12.01</b>	39121542
<b>UNSPSC 13.2</b>	39121542


## approvals

---

UL Recognized / UL Listed / cUL Recognized / GOST / cUL Listed / GL / cULus Recognized / cULus Listed /





---

### Approval details



# Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

approvals



accessories

## Mounting rail

NS 35/ 7,5 V2A UNPERF 2000MM - 0801377



## Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

### accessories

NS 35/ 7,5 PERF 2000MM - 0801733



---

NS 35/ 7,5 CU UNPERF 2000MM - 0801762



---

NS 35/15 UNPERF 2000MM - 1201714



---

NS 35/15 CU UNPERF 2000MM - 1201895



---

NS 35/15-2,3 UNPERF 2000MM - 1201798



## Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

### accessories

NS 35/15 AL UNPERF 2000MM - 1201756



NS 35/15 PERF 2000MM - 1201730



NS 35/ 7,5 UNPERF 2000MM - 0801681



### Terminal marking

ZB 6/WH-100:UNBEDRUCKT - 5060935



ZB 6:UNBEDRUCKT - 1051003



### Labeled terminal marker

# Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

## accessories

ZB 6,LGS:FORTL.ZAHLEN - 1051016



---

### Partition plate

PLC-ATP BK - 2966841



---

### Power module

PLC-ESK GY - 2966508



---

### Screwdriver tools

SZF 1-0,6X3,5 - 1204517



---

### Controller board

## Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

### accessories

PLC-V8/FLK14/IN - 2296553



PLC-V8/FLK14/IN/M - 2304115



PLC-V8/D15B/IN - 2296087



### Interface module

PLC-V8/D15S/IN - 2296074



### Relay socket

PLC-BSC- 24DC/ 1/SEN - 2966061





# Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

accessories

**Single solid-state relay**

OPT-24DC/ 48DC/100 - 2966618



---

## Bridge

FBST 500-PLC RD - 2966786



---

FBST 500-PLC BU - 2966692



---

FBST 500-PLC GY - 2966838



---

FBST 6-PLC RD - 2966236



## Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

### accessories

FBST 6-PLC BU - 2966812



FBST 6-PLC GY - 2966825



FBST 8-PLC GY - 2967688



### Drawings

# Solid-state relay module - PLC-OSC- 24DC/ 48DC/100/ SEN - 2966773

Circuit diagram

