

## Disconnect terminal block - UT 4-HEDI - 3046249

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Disconnect terminal block, Connection type: Screw connection, Cross section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 26 - 10, Nominal current: 20 A, Nominal voltage: 500 V, Length: 57.8 mm, Width: 6.2 mm, Color: Black/orange, Assembly: NS 35/7,5, NS 35/15

### Product Features

- ☒ An extremely compact design
- ☒ Tested for railway applications
- ☒ Test connection on both sides in safety lever

### Key commercial data

|                  |               |
|------------------|---------------|
| package_quantity | 50            |
| GTIN             | 4017918960940 |

### Technical data

#### General

|                                         |                        |
|-----------------------------------------|------------------------|
| Number of levels                        | 1                      |
| Number of connections                   | 2                      |
| Color                                   | Black/orange           |
| Insulating material                     | PA                     |
| Inflammability class according to UL 94 | V0                     |
| Area of application                     | Railway industry       |
| Area of application                     | Mechanical engineering |
| Area of application                     | Plant engineering      |

#### General

|                                     |                                                       |
|-------------------------------------|-------------------------------------------------------|
| Maximum load current                | 16 A (with 6 mm <sup>2</sup> conductor cross section) |
| Rated surge voltage                 | 6 kV                                                  |
| Pollution degree                    | 3                                                     |
| Surge voltage category              | III                                                   |
| Insulating material group           | I                                                     |
| Connection in acc. with standard    | IEC 60947-7-1                                         |
| Nominal current I <sub>N</sub>      | 20 A                                                  |
| Nominal voltage U <sub>N</sub>      | 500 V                                                 |
| Open side panel                     | nein                                                  |
| Shock protection test specification | DIN EN 50274 (VDE 0660-514):2002-11                   |
| Back of the hand protection         | guaranteed                                            |

# Disconnect terminal block - UT 4-HEDI - 3046249

## Technical data

### General

|                                                                                 |                                                     |
|---------------------------------------------------------------------------------|-----------------------------------------------------|
| Finger protection                                                               | guaranteed                                          |
| Surge voltage test setpoint                                                     | 7.3 kV                                              |
| Result of surge voltage test                                                    | Test passed                                         |
| Power frequency withstand voltage setpoint                                      | 1.89 kV                                             |
| Result of power-frequency withstand voltage test                                | Test passed                                         |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed                                         |
| Bending test rotation speed                                                     | 10 rpm                                              |
| Bending test turns                                                              | 135                                                 |
| Bending test conductor cross section/weight                                     | 0.14 mm <sup>2</sup> / 0.2 kg                       |
| Bending test conductor cross section/weight                                     | 4 mm <sup>2</sup> / 0.9 kg                          |
| Bending test conductor cross section/weight                                     | 6 mm <sup>2</sup> / 1.4 kg                          |
| Result of bending test                                                          | Test passed                                         |
| Conductor cross section tensile test                                            | 0.14 mm <sup>2</sup>                                |
| Tractive force setpoint                                                         | 10 N                                                |
| Conductor cross section tensile test                                            | 4 mm <sup>2</sup>                                   |
| Tractive force setpoint                                                         | 60 N                                                |
| Conductor cross section tensile test                                            | 6 mm <sup>2</sup>                                   |
| Tractive force setpoint                                                         | 80 N                                                |
| Tensile test result                                                             | Test passed                                         |
| Tight fit on carrier                                                            | NS 35                                               |
| Setpoint                                                                        | 1 N                                                 |
| Result of tight fit test                                                        | Test passed                                         |
| Result of voltage drop test                                                     | Test passed                                         |
| Temperature-rise test                                                           | Test passed                                         |
| Conductor cross section short circuit testing                                   | 4 mm <sup>2</sup>                                   |
| Short-time current                                                              | 0.48 kA                                             |
| Short circuit stability result                                                  | Test passed                                         |
| Proof of thermal characteristics (needle flame) effective duration              | 30 s                                                |
| Result of thermal test                                                          | Test passed                                         |
| Test specification, oscillation, broadband noise                                | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Test spectrum                                                                   | Service life test category 1, class B, body mounted |
| Test frequency                                                                  | f <sub>1</sub> = 5 Hz to f <sub>2</sub> = 150 Hz    |
| ASD level                                                                       | 0.02 g <sup>2</sup> /Hz                             |
| Acceleration                                                                    | 0.8 g                                               |
| Test duration per axis                                                          | 5 h                                                 |
| Test directions                                                                 | X-, Y- and Z-axis                                   |
| Oscillation, broadband noise test result                                        | Test passed                                         |
| Test specification, shock test                                                  | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Shock form                                                                      | Half-sine                                           |
| Acceleration                                                                    | 5 g                                                 |

# Disconnect terminal block - UT 4-HEDI - 3046249

## Technical data

### General

|                                                                       |                                   |
|-----------------------------------------------------------------------|-----------------------------------|
| Shock duration                                                        | 30 ms                             |
| Number of shocks per direction                                        | 3                                 |
| Test directions                                                       | X-, Y- and Z-axis (pos. and neg.) |
| Shock test result                                                     | Test passed                       |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 120 °C                            |

### Dimensions

|                  |         |
|------------------|---------|
| Width            | 6.2 mm  |
| Length           | 57.8 mm |
| Height NS 35/7,5 | 73 mm   |
| Height NS 35/15  | 80.5 mm |

### Connection data

|                                                                                         |                      |
|-----------------------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                                      | 6 mm <sup>2</sup>    |
| Conductor cross section AWG/kcmil min.                                                  | 26                   |
| Conductor cross section AWG/kcmil max                                                   | 10                   |
| Conductor cross section stranded min.                                                   | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded max.                                                   | 6 mm <sup>2</sup>    |
| Min. AWG conductor cross section, stranded                                              | 26                   |
| Max. AWG conductor cross section, stranded                                              | 10                   |
| Conductor cross section stranded, with ferrule without plastic sleeve min.              | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max.              | 4 mm <sup>2</sup>    |
| Conductor cross section stranded, with ferrule with plastic sleeve min.                 | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max.                 | 4 mm <sup>2</sup>    |
| 2 conductors with same cross section, solid min.                                        | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.                                        | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded min.                                     | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                     | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1.5 mm <sup>2</sup>  |
| Connection method                                                                       | Screw connection     |
| Stripping length                                                                        | 9 mm                 |
| Internal cylindrical gage                                                               | A4                   |

# Disconnect terminal block - UT 4-HEDI - 3046249

## Technical data

### Connection data

|                               |        |
|-------------------------------|--------|
| <b>Screw thread</b>           | M3     |
| <b>Tightening torque, min</b> | 0.6 Nm |
| <b>Tightening torque max</b>  | 0.8 Nm |

## classifications

### eCl@ss

|                   |          |
|-------------------|----------|
| <b>eCl@ss 4.0</b> | 27141117 |
| <b>eCl@ss 4.1</b> | 27141117 |
| <b>eCl@ss 5.0</b> | 27141120 |
| <b>eCl@ss 5.1</b> | 27141120 |
| <b>eCl@ss 6.0</b> | 27141120 |
| <b>eCl@ss 7.0</b> | 27141120 |
| <b>eCl@ss 8.0</b> | 27141120 |

### ETIM

|                 |          |
|-----------------|----------|
| <b>ETIM 2.0</b> | EC000902 |
| <b>ETIM 3.0</b> | EC000902 |
| <b>ETIM 4.0</b> | EC000902 |
| <b>ETIM 5.0</b> | EC000902 |

### UNSPSC

|                      |          |
|----------------------|----------|
| <b>UNSPSC 6.01</b>   | 30211811 |
| <b>UNSPSC 7.0901</b> | 39121410 |
| <b>UNSPSC 11</b>     | 39121410 |
| <b>UNSPSC 12.01</b>  | 39121410 |
| <b>UNSPSC 13.2</b>   | 39121410 |

## approvals

CSA / UL Recognized / cUL Recognized / LR / GL / DNV / RS / cULus Recognized /

### Approval details

|  |       |       |
|-------------------------------------------------------------------------------------|-------|-------|
| Usegroups                                                                           | B     | C     |
| Nominal voltage UN                                                                  | 600 V | 600 V |
| Nominal current IN                                                                  | 16 A  | 16 A  |
| mm²/AWG/kcmil                                                                       | 26-10 | 26-10 |

## Disconnect terminal block - UT 4-HEDI - 3046249

### approvals

| UL Recognized  |       |       |
|-------------------------------------------------------------------------------------------------|-------|-------|
| Usegroups                                                                                       | B     | C     |
| Nominal voltage UN                                                                              | 600 V | 600 V |
| Nominal current IN                                                                              | 16 A  | 16 A  |
| mm²/AWG/kcmil                                                                                   | 26-10 | 26-10 |

| cUL Recognized  |       |       |
|--------------------------------------------------------------------------------------------------|-------|-------|
| Usegroups                                                                                        | B     | C     |
| Nominal voltage UN                                                                               | 600 V | 600 V |
| Nominal current IN                                                                               | 16 A  | 16 A  |
| mm²/AWG/kcmil                                                                                    | 26-10 | 26-10 |

|    |
|----|
| LR |
|----|

|    |
|----|
| GL |
|----|

|     |
|-----|
| DNV |
|-----|

|    |
|----|
| RS |
|----|

|                                                                                                         |
|---------------------------------------------------------------------------------------------------------|
| cULus Recognized  US |
|---------------------------------------------------------------------------------------------------------|

### accessories

#### Screwdriver tools

SZS 0,6X3,5 - 1205053



#### Marker pen

## Disconnect terminal block - UT 4-HEDI - 3046249

### accessories

B-STIFT - 1051993



---

X-PEN 0,35 - 0811228



---

### Bridge

VS - 3004207



---

FBS 2-6 - 3030336



---

FBS 3-6 - 3030242



## Disconnect terminal block - UT 4-HEDI - 3046249

### accessories

FBS 4-6 - 3030255



---

FBS 5-6 - 3030349



---

FBS 10-6 - 3030271



---

FBS 20-6 - 3030365



---

### Mounting rail

NS 35/ 7,5 PERF 2000MM - 0801733



## Disconnect terminal block - UT 4-HEDI - 3046249

### accessories

NS 35/ 7,5 UNPERF 2000MM - 0801681



---

NS 35/ 7,5 WH PERF 2000MM - 1204119



---

NS 35/ 7,5 WH UNPERF 2000MM - 1204122



---

NS 35/ 7,5 AL UNPERF 2000MM - 0801704



---

NS 35/ 7,5 ZN PERF 2000MM - 1206421



---

NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



## Disconnect terminal block - UT 4-HEDI - 3046249

### accessories

---

NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



NS 35/15 PERF 2000MM - 1201730



NS 35/15 UNPERF 2000MM - 1201714



NS 35/15 WH PERF 2000MM - 0806602



## Disconnect terminal block - UT 4-HEDI - 3046249

### accessories

NS 35/15 WH UNPERF 2000MM - 1204135



NS 35/15 AL UNPERF 2000MM - 1201756



NS 35/15 ZN PERF 2000MM - 1206599



NS 35/15 ZN UNPERF 2000MM - 1206586



NS 35/15 CU UNPERF 2000MM - 1201895



NS 35/15 CAP - 1206573



## Disconnect terminal block - UT 4-HEDI - 3046249

### accessories

---

NS 35/15-2,3 UNPERF 2000MM - 1201798



---

### Terminal marking

ZB 5 :UNBEDRUCKT - 1050004



---

UC-TM 5 - 0818108



---

UCT-TM 5 - 0828734



---

ZB 6:UNBEDRUCKT - 1051003



## Disconnect terminal block - UT 4-HEDI - 3046249

### accessories

UC-TM 6 - 0818085



---

UCT-TM 6 - 0828736



---

### Labeled terminal marker

ZB 5 CUS - 0824962



---

UC-TM 5 CUS - 0824581



---

UCT-TM 5 CUS - 0829595



## Disconnect terminal block - UT 4-HEDI - 3046249

### accessories

ZB 6 CUS - 0824992



---

UC-TM 6 CUS - 0824589



---

UCT-TM 6 CUS - 0829602



---

### End block

CLIPFIX 35 - 3022218



---

CLIPFIX 35-5 - 3022276



## Disconnect terminal block - UT 4-HEDI - 3046249

accessories


E/NS 35 N - 0800886



---

### Drawings

Circuit diagram



© Phoenix Contact 2013 - all rights reserved  
<http://www.phoenixcontact.com>