

Component connector - ST-1N4007 - 2802329

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Component plug, with universal diode, to connect 2-pos. components into the basic terminal block, height: 19 mm, color: Gray

Key commercial data

package_quantity	10
GTIN	4017918074418

Technical data

General

Color	gray
Insulating material	PA
Inflammability class according to UL 94	V0

Dimensions

Height	19 mm
--------	-------

Connection data

Stripping length	7 mm
Tightening torque, min	0.3 Nm
Tightening torque max	0.4 Nm

classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141149

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018

Component connector - ST-1N4007 - 2802329

classifications

ETIM

ETIM 5.0	EC002018
-----------------	----------

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

approvals

UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized /

Approval details

UL Recognized 	
Nominal voltage UN	300 V
Nominal current IN	1 A
mm²/AWG/kcmil	30-14

cUL Recognized 	
Nominal voltage UN	300 V
Nominal current IN	1 A
mm²/AWG/kcmil	30-14

GOST 



cULus Recognized 

Component connector - ST-1N4007 - 2802329

accessories

Documentation

ST-IL - 3039900



Drawings

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>