


Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ground modular terminal block, Connection method: Spring-cage connection, Cross section: 0.08 mm² - 4 mm², AWG: 28 - 12, Width: 5.2 mm, Color: green-yellow, Mounting type: NS 35/7,5, NS 35/15

Product Features

- Additional labeling options
- Tested for railway applications
- Corrosion-free terminal points
- Low contact resistance
- Green-yellow housing



Key commercial data

package_quantity	50
GTIN	4017918186777

Technical data

General

Number of levels	1
Number of connections	3
Color	green-yellow
Insulating material	PA
Inflammability class according to UL 94	V0
Area of application	Railway industry
Area of application	Mechanical engineering
Area of application	Plant engineering
Area of application	Process industry

General

Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-2

Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

Technical data

General

Open side panel	ja
-----------------	----

Dimensions

Width	5.2 mm
Length	60.5 mm
Height NS 35/7,5	36.5 mm
Height NS 35/15	44 mm

Connection data

Conductor cross section solid min.	0.08 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG/kcmil min.	28
Conductor cross section AWG/kcmil max	12
Conductor cross section stranded min.	0.08 mm ²
Conductor cross section stranded max.	2.5 mm ²
Min. AWG conductor cross section, stranded	28
Max. AWG conductor cross section, stranded	14
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.14 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	2.5 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.14 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	2.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	0.5 mm ²
Connection method	Spring-cage connection
Minimum stripping length	8 mm
Maximum stripping length	10 mm
Internal cylindrical gage	A3

classifications

eCl@ss

eCl@ss 4.0	27141118
eCl@ss 4.1	27141118
eCl@ss 5.0	27141118
eCl@ss 5.1	27141118
eCl@ss 6.0	27141141
eCl@ss 7.0	27141141
eCl@ss 8.0	27141141

ETIM

ETIM 2.0	EC000901
----------	----------

Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

classifications

ETIM

ETIM 3.0	EC000901
ETIM 4.0	EC000901
ETIM 5.0	EC000901

UNSPSC


UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410


approvals

IECEX / ATEX / CSA / UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / GOST / LR / GL / BV / DNV / RS / ABS / KR / NK / IECEE CB Scheme / VDE Gutachten mit Fertigungsüberwachung / IECEE CB Scheme / GOST / cULus Recognized /

Approval details


IECEX	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	0.08-2.5


ATEX 	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	0.08-4


CSA 	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	28-12


Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

approvals

UL Recognized 	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	28-12

VDE Gutachten mit Fertigungsüberwachung 	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	0.2-2.5

cUL Recognized 	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	28-12

GOST 	
-------------------------------------------------------------------------------------------------	--

LR

GL	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	2.5

BV

DNV

RS


Ground modular terminal block - ST 2,5-TWIN-PE - 3031267


approvals


ABS	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	26-12

KR


NK

IECEE CB Scheme 	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	0.2-2.5

	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	0.2-2.5

	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	0.2-2.5

	
-------------------------------------------------------------------------------------	--

cULus Recognized 	
-------------------------------------------------------------------------------------------------------------	--

Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

Marker pen

B-STIFT - 1051993



X-PEN 0,35 - 0811228



End cover

D-ST 2,5-TWIN - 3030488



DS-ST 2,5 - 3036602



D-ST 2,5-TWIN-0,8 OG - 3030512



Partition plate

Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

ATP-ST-TWIN - 3030789



Screwdriver tools

SZF 1-0,6X3,5 - 1204517



Documentation

ST-IL - 3039900



Bridge

FBS 20-5 - 3030226



FBS 10-5 - 3030213



Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

FBS 5-5 - 3030190



FBS 4-5 - 3030187



FBS 3-5 - 3030174



FBS 2-5 - 3030161



FBS 50-5 - 3038930



Mounting rail

Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

NS 35/ 7,5 PERF 2000MM - 0801733



NS 35/ 7,5 UNPERF 2000MM - 0801681



NS 35/ 7,5 WH PERF 2000MM - 1204119



NS 35/ 7,5 WH UNPERF 2000MM - 1204122



NS 35/ 7,5 AL UNPERF 2000MM - 0801704



NS 35/ 7,5 ZN PERF 2000MM - 1206421



Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



NS 35/15 PERF 2000MM - 1201730



NS 35/15 UNPERF 2000MM - 1201714



Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

NS 35/15 WH PERF 2000MM - 0806602



NS 35/15 WH UNPERF 2000MM - 1204135



NS 35/15 AL UNPERF 2000MM - 1201756



NS 35/15 ZN PERF 2000MM - 1206599



NS 35/15 ZN UNPERF 2000MM - 1206586



NS 35/15 CU UNPERF 2000MM - 1201895



Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

NS 35/15 CAP - 1206573



NS 35/15-2,3 UNPERF 2000MM - 1201798



Terminal marking

ZB 5 :UNBEDRUCKT - 1050004



UC-TM 5 - 0818108



UCT-TM 5 - 0828734



Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

ZBF 5:UNBEDRUCKT - 0808642



UC-TMF 5 - 0818153



UCT-TMF 5 - 0828744



Labeled terminal marker

ZB 5 CUS - 0824962



UC-TM 5 CUS - 0824581



Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

UCT-TM 5 CUS - 0829595



ZBF 5 CUS - 0825025



UC-TMF 5 CUS - 0824638



UCT-TMF 5 CUS - 0829658



Insulating sleeve

ISH 2,5/0,2 - 3002843



Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

ISH 2,5/0,5 - 3002856



ISH 2,5/1,0 - 3002869



End block

CLIPFIX 35 - 3022218



CLIPFIX 35-5 - 3022276



E/NS 35 N - 0800886



Ground modular terminal block - ST 2,5-TWIN-PE - 3031267

accessories

E/UK - 1201442



E/UK 1 - 1201413



Drawings

Circuit diagram

