



**Notes:**

- Electrical Specifications:
  - Meets EIA/TIA-568-B.2 Cat.5e Specification
  - Contact Resistance: 20mOhm max.
  - Insulation Resistance: 500MOhm min. @ 100 VDC
  - Current Rating: 1.2A max. at 25°C
  - Working Voltage: 100 VDC
  - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
  - Operating Temperature: -40°C to +85°C
- Material and Finish:
  - Receptacle Housing: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
  - Cover Coupling Ring: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
  - Panel Nut: Brass, Finish: Nickel Plated
  - Panel Gasket: Silicone, Color: White
  - Cover Gasket: Silicone, Color: Red
  - Tether: Polycarbonate, Color: Black
  - RJ45 Jack Metal Shell: Copper Alloy, Nickel Plated
  - RJ45 Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
  - RJ45 Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
- Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- RoHS compliant

Directive 2002/95/EC  
"RoHS"  
Compliant

Description	Part Number
Plastic Version with Shielded RJ45 Inline Coupler with Cover	17-10000
Plastic Version with Unshielded RJ45 Inline Coupler with Cover	17-10020
Metallized Plastic Version with Shielded RJ45 Inline Coupler with Cover	17-10011

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. <b>DO NOT ALTER CAD DRAWING BY HAND</b>	Customer:			Tolerance Unless otherwise specified			Scale: 1:2:1	Dim. in mm
	Name	Title	Approval Date	0 PLC ±0.50	1 PLC ±0.38		Autodesk Inventor	Material: See Notes
				2 PLC ±0.25	3 PLC ±0.10		File: Receptacle & Cover Assembly Kit	
	e	Jan/28/08	Vincent Ke	Angles ±3	Draw. Oct 24	Vincent Ke	Industrial Ethernet Connector (IP67)	
	d	Sept/18/07	Vincent Ke		Appd. Oct 24	J. Chaudry	with Cat. 5e RJ45 Inline Coupler	
c	May/15/07	Vincent Ke				Drawing No.: 39K1A203	DIN A3	
b	Mar/08/07	Vincent Ke				Part No.: SEE P/N ABOVE	Sheet 1/1	
a	origin							
Rev.	Changes	Date	Name	<b>CONEC</b>				