



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
 5. BERYLLIUM COPPER PER QQ-C-530
 6. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 7. TEFLON MIL-P-19468

11	SHELL	NOTE 1	NOTE 3	1	SMA5000-1-C
10	GASKET	SILICONE	RED		GS-6/43X06
9	RETAINER RING	NOTE 5	NATURAL	1	SMA5000-4-B
8	SHELL	NOTE 1	NOTE 3	1	B50000-1-B
7	GASKET	RUBBER	RED	1	GS-115/8X15
6	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
5	SPRING	SK5	NOTE 4	1	B50000-6
4	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
3	CONTACT PIN	NOTE 1	NOTE 6	1	RSA-3459-3
2	INSULATOR	NOTE 7	NATURAL	1	RSA-3459-2
1	BODY	NOTE 1	NOTE 3	1	RSA-3459-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			PART NO.	SMAM-BM-NT3G-50	
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4			APPROVED	DATE	10-11-01'
			CHECKED	DATE	10-11-01'
			DRAWN	DATE	10-11-01'
			SCALE	4/1	ISSUE

Amphenol	
TITLE SMA MALE TO BNC MALE ADAPTOR	
DRAWING NO. KJ-SMAM-BM-NT3G-50	
ITEM NO.	