

Connector - Q 0,75/4IDC/18-18KU-KU BK - 1642140

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



QUICKON conductor connector, 4-pos., connection cross section 0.34-0.75 mm²

Product Features

- Innovative and time saving - QUICKON fast connection for time saving of up to 80% for on-site connection
- Convenient: quick and easy assembly without special tools
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection thanks to polarization against mismatching and touch-proof protection according to DIN EN 0105
- Easy and safe - with the cable connector, you can repair or extend cables quickly, in combination with the connector as well as the coupling connection

Key commercial data

package_quantity	1
GTIN	4017918923891

Technical data

General

Color	black
Connection method	QUICKON connection
Connection method	IDC connection
Number of positions	4
Wrench size, union nut	15 mm
Tightening torque, union nut	1.2 Nm
Wrench size, contact carrier	15 mm
Conductor cross section stranded min.	0.34 mm ²
Conductor cross section stranded max.	0.75 mm ²
Conductor cross section solid min.	0.34 mm ²
Conductor cross section solid max.	0.5 mm ²
Conductor cross section AWG/kcmil min.	22
Conductor cross section AWG/kcmil max	18

Conductor

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	VDE 0295 class 1 to 6 / min. 0.15 mm
Wire insulation material	PVC/PE
Wire diameter including insulation	1.3 mm ... 2.6 mm

Connector - Q 0,75/4IDC/18-18KU-KU BK - 1642140

Technical data

Conductor

External cable diameter	4 mm ... 8 mm
-------------------------	---------------

Ambient conditions

Degree of protection	IP65
Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 80 °C (specifications of the cable manufacturer must also be observed)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Temperature when conductor connected	-5 °C ... 50 °C (specifications of the cable manufacturer must also be observed)

Electrical characteristics

Nominal current I_N	9 A
Rated current	9 A
Rated voltage (III/3)	250 V
Rated voltage (III/2)	400 V
Rated voltage (II/2)	500 V
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV

Mechanical characteristics

QUICKON connectability	max. 10
------------------------	---------

Material data

Contact material	Steel
Contact surface material	Tin-plated
Contact carrier material	PA
Insulating material	PA
Inflammability class according to UL 94	V0
Surge voltage category	III
Pollution degree	3

classifications

eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 7.0	27449001
eCl@ss 8.0	27449001

ETIM

Connector - Q 0,75/4IDC/18-18KU-KU BK - 1642140

classifications

ETIM

ETIM 2.0	EC000516
ETIM 3.0	EC000516
ETIM 4.0	EC000516
ETIM 5.0	EC000516

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

approvals

UL Recognized / VDE Zeichengenehmigung / cUL Recognized / GOST / cULus Recognized /

Approval details

UL Recognized	
Nominal voltage UN	250 V
Nominal current IN	9 A
mm ² /AWG/kcmil	22-18

VDE Zeichengenehmigung	
Nominal voltage UN	400 V
Nominal current IN	
mm ² /AWG/kcmil	

cUL Recognized	
Nominal voltage UN	250 V
Nominal current IN	6 A
mm ² /AWG/kcmil	22-18

Connector - Q 0,75/4IDC/18-18KU-KU BK - 1642140

approvals



accessories

Socket spanner

QSS 15 - 1641992



Sealing plugs

SEALING PLUG 8X16 RD - 1400257



accessories


MICROFOX SC - 1205862



Drawings

Connector - Q 0,75/4IDC/18-18KU-KU BK - 1642140

Dimensioned drawing



© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>