

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

LM 48 Montagepaste 50 g
Art.: 3010

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr
Telephone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Di-iso-octyl amino methyl tolutriazole. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

3.1 Substance

n.a.

3.2 Mixture

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	--
Index	606-001-00-8
EINECS, ELINCS, NLP	200-662-2
CAS	CAS 67-64-1
content %	1-5
Classification according to Directive 67/548/EEC	Highly flammable, F, R11 Irritant, Xi, R36 R66 R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Tungsten disulphide	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	235-243-3
CAS	CAS 12138-09-9
content %	1-5
Classification according to Directive 67/548/EEC	Irritant, Xi, R36/37/38
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Not required.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

With long-term contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

Allergic reaction

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Page 3 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 14.01.2014 / 0011
Replaces revision of / Version: 28.11.2012 / 0010
Valid from: 14.01.2014
PDF print date: 15.01.2014
LM 48 Montagepaste 50 g Art.: 3010

CO2
Dry extinguisher
Foam
Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Oxides of sulphur
Hydrocarbons
Toxic pyrolysis products.
Hot product gives off combustible vapours.

5.3 Advice for firefighters

Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.
Avoid formation of oil mist.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping
Do not carry cleaning cloths soaked in product in trouser pockets.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Do not heat to temperatures close to flash point.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Solvent resistant floor
Do not store with oxidizing agents.
Store in a well ventilated place.
Protect from direct sunlight and warming.
Store in a dry place.

GB

Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Acetone		Content %:1-5
WEL-TWA:	500 ppm (1210 mg/m ³) (WEL, EU)	WEL-STEL:	1500 ppm (3620 mg/m ³) (WEL)
BMGV:	---	Other information:	---
Chemical Name	Tungsten disulphide		Content %:1-5
WEL-TWA:	5 mg/m ³ (insoluble compounds as W)	WEL-STEL:	10 mg/m ³ (insoluble compounds as W)
BMGV:	---	Other information:	---
Chemical Name	Calcium fluoride		Content %:
WEL-TWA:	2,5 mg/m ³ (fluoride (inorganic, as F) (WEL, EU)	WEL-STEL:	---
BMGV:	---	Other information:	---
Chemical Name	Oil mist, mineral		Content %:
WEL-TWA:	5 mg/m ³ (ACGIH)	WEL-STEL:	10 mg/m ³ (ACGIH)
BMGV:	---	Other information:	---

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Acetone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term	DNEL	2420	mg/m ³	
Workers / employees	Human - inhalation	Long term	DNEL	1210	mg/m ³	
Consumer	Human - oral	Long term	DNEL	62	mg/kg bw/day	
Consumer	Human - dermal	Long term	DNEL	62	mg/kg bw/day	
Consumer	Human - inhalation	Long term	DNEL	200	mg/m ³	
	Environment - marine		PNEC	1,06	mg/l	
	Environment - freshwater		PNEC	10,6	mg/l	
	Environment - sediment, freshwater		PNEC	30,4	mg/l	
	Environment - sediment, marine		PNEC	3,04	mg/l	
	Environment - soil		PNEC	0,112	mg/l	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

GB

Page 5 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Protective gloves, oil resistant (EN 374)
 If applicable
 Protective nitrile gloves (EN 374)
 Minimum layer thickness in mm:
 0,4

Permeation time (penetration time) in minutes:
 > 480
 The breakthrough times determined in accordance with EN 374 Part III were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Filter A2 P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Pastelike, Liquid
Colour:	Black
Odour:	Odourless
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	101 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1 g/ml (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined

(GB)

Page 6 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	>7 mm ² /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.
 Not to be expected

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7.
 Open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

LM 48 Montagepaste 50 g
Art.: 3010

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Acetone

Page 7 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3000	mg/kg	Mouse		
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	20000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	32	mg/m ³	Rat		
Skin corrosion/irritation:						Slightly irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit		Irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitizing
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Symptoms:						unconsciousness, vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea

Tungsten disulphide						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Irritant
Respiratory tract irritation:						Irritation of the respiratory tract

Calcium fluoride						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4250	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Symptoms:						ataxia, respiratory distress, drop in blood pressure, diarrhoea, thirst, headaches, muscle weakness, nausea and vomiting.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

LM 48 Montagepaste 50 g Art.: 3010							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							Mechanical precipitation possible.

GB

Page 8 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment:							n.d.a.
Other adverse effects:							n.d.a.

Acetone							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus mykiss		
Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
Toxicity to fish:	LC50	96h	5540-8300	mg/l	Lepomis macrochirus		
Toxicity to daphnia:	EC50	48h	6100-12700	mg/l	Daphnia magna		
Toxicity to algae:	IC50	8d	7500	mg/l	Scenedesmus quadricauda		
Toxicity to algae:	EC50	96h	7500	mg/l	Selenastrum capricornutum		
Toxicity to algae:	NOEC/NO EL	48h	3400	mg/l	Pseudokirchneriella subcapitata		
Persistence and degradability:		28d	91	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
Bioaccumulative potential:	Log Pow		-0,24				
Bioaccumulative potential:	BCF		0,19				
Mobility in soil:							No adsorption in soil.
Results of PBT and vPvB assessment:							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC5	16h	1700	mg/l	Pseudomonas putida		
Toxicity to bacteria:	EC5	8d	530	mg/l	Microcystis aeruginosa		
Other information:	AOX		0	%			
Other information:	BOD5		1900	mg/g			
Other information:	COD		2100	mg/g			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

(GB)

Page 9 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Classification code: n.a.

LQ (ADR 2013): n.a.

LQ (ADR 2009): n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Marine Pollutant: n.a.

Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: n.a.

VOC 1999/13/EC: < 1,8%

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: 2, 8

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

11 Highly flammable.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

36/37/38 Irritating to eyes, respiratory system and skin.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Page 10 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

Flam. Liq. — Flammable liquid
 Eye Irrit. — Eye irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Skin Irrit. — Skin irritation
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential

Page 11 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.01.2014 / 0011
 Replaces revision of / Version: 28.11.2012 / 0010
 Valid from: 14.01.2014
 PDF print date: 15.01.2014
 LM 48 Montagepaste 50 g Art.: 3010

HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone
 ThOD Theoretical oxygen demand
 TOC Total organic carbon
 TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
 WHO World Health Organization
 wwt wet weight

GB

Page 12 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 14.01.2014 / 0011
Replaces revision of / Version: 28.11.2012 / 0010
Valid from: 14.01.2014
PDF print date: 15.01.2014
LM 48 Montagepaste 50 g Art.: 3010

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.