

Interface module - VIP-2/SC/PDM-2/32 - 2315272

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



VARIOFACE module, with two equipotential busbars (P1, P2) for potential distribution, for mounting on NS 35 rails. Module width: 90.8 mm

Product Features

- ☒ Consecutive numbering
- ☒ Separate supply
- ☒ Two potential levels



Key commercial data

package_quantity	1
GTIN	4046356313094

Technical data

Dimensions

Width	90.8 mm
Height	65.5 mm
Depth	50 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Nominal voltage U_N	250 V AC/DC
Max. current carrying capacity per branch	15 A
Total current	30 A (Per potential)
Potential connections	Per potential (P1, P2) 2 power/16 distributor terminal blocks
Mounting position	Any
Standards/regulations	IEC 60664
Standards/regulations	DIN EN 50178
Standards/regulations	IEC 62103
Pollution degree	2
Surge voltage category	III

Interface module - VIP-2/SC/PDM-2/32 - 2315272

Technical data

Connection data, supply

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	6 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	10
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3

Connection data, distribution

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3

classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27242608
eCl@ss 8.0	27242608

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC001604

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421

Interface module - VIP-2/SC/PDM-2/32 - 2315272

classifications

UNSPSC

UNSPSC 13.2	39121421
--------------------	----------

approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized /

Approval details

CSA 	
Nominal voltage UN	250 V
Nominal current IN	12 A
mm²/AWG/kcmil	30-10

UL Recognized 	
Nominal voltage UN	250 V
Nominal current IN	12 A
mm²/AWG/kcmil	30-10

cUL Recognized 	
Nominal voltage UN	250 V
Nominal current IN	12 A
mm²/AWG/kcmil	30-10

cULus Recognized 	
--	--

Drawings

Interface module - VIP-2/SC/PDM-2/32 - 2315272

Circuit diagram

