

* 1 Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· **Trade name: CARAMBA Profi High performance special-purpose remover (Aerosol)**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the preparation** Cleaning agent/ Cleaner

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

CARAMBA CHEMIE GMBH & Co.KG

WANHEIMERSTR. 334/336

47055 DUISBURG

www.caramba.de

Tel.: +49 (0) 203/77 86 01

· Further information obtainable from:

Abteilung Labor

Andrea Petersen

andrea.petersen@caramba.de

Tel.: +49 (0)203 / 77 86-189

· 1.4 Emergency telephone number:

Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch

2 Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Sensitising

R43: May cause sensitisation by skin contact.



F+; Extremely flammable

R12: Extremely flammable.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xi Irritant

F+ Extremely flammable

N Dangerous for the environment

· **Hazard-determining components of labelling:**

(R)-p-mentha-1,8-diene

· **Risk phrases:**

12 Extremely flammable.

Trade name: CARAMBA Profi High performance special-purpose remover (Aerosol)

(Contd. of page 1)

- 43 May cause sensitisation by skin contact.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

Safety phrases:

- 2 Keep out of the reach of children.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe spray.
24 Avoid contact with skin.
51 Use only in well-ventilated areas.
60 This material and its container must be disposed of as hazardous waste.

Special labelling of certain preparations:

- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Buildup of explosive mixtures possible without sufficient ventilation.

Classification in accordance with Directive 75/324/EEC: Extremely flammable
2.3 Other hazards
Results of PBT and vPvB assessment

- PBT:** Not applicable.
vPvB: Not applicable.

3 Composition/information on ingredients

3.2 Chemical characterization: Mixtures

- Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-48-9 EC number: 927-241-2	Naphtha (petroleum), hydrotreated heavy Xn R65 R10-52/53-66-67 Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412	20-40%
CAS: 64742-49-0 EC number: 920-750-0	Naphtha (Erdöl), mit Wasserstoff behandelte leichte (Anmerkung:P) Xn R65; F R11; N R51/53 R66-67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411	10-20%
CAS: 106-97-8 EINECS: 203-448-7	butane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	10-20%
CAS: 5989-27-5 EINECS: 227-813-5	(R)-p-mentha-1,8-diene Xi R38; Xi R43; N R50/53 R10 Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	5-10%
CAS: 74-98-6 EINECS: 200-827-9	propane F+ R12 Flam. Gas 1, H220; Flam. Liq. 1, H224; Press. Gas, H280	2.5-5%
CAS: 75-28-5 EINECS: 200-857-2	isobutane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	1-2.5%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons	≥ 30%
perfumes (LIMONENE)	

(Contd. on page 3)

Trade name: CARAMBA Profi High performance special-purpose remover (Aerosol)

(Contd. of page 2)

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

(Contd. on page 4)

Trade name: CARAMBA Profi High performance special-purpose remover (Aerosol)

(Contd. of page 3)

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane (10-25%)

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:** Not required.
- **Protection of hands:** Protective gloves
- **Material of gloves:** Nitrile rubber, NBR
- **Penetration time of glove material:** Value for the permeation: Level ≤ 480 min
- **Eye protection:** Tightly sealed goggles

9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

General Information

Appearance:

Form:	Aerosol
Colour:	Colourless
Odour:	Fruit-like
Odour threshold:	Not determined.

- **pH-value:** Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.

- **Flash point:** -71 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

- **Vapour pressure:** Not determined.

(Contd. on page 5)

Trade name: CARAMBA Profi High performance special-purpose remover (Aerosol)

(Contd. of page 4)

· Density at 20 °C:	0.75 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
VOC (EC)	98.90 %
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-49-0 Naphtha (Erdöl), mit Wasserstoff behandelte leichte (Anmerkung:P)

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	< 3000 mg/kg (rabbit)
Inhalative	LC50/4 h	12 mg/l (rat)

5989-27-5 (R)-p-mentha-1,8-diene

Oral	LD50	4400 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 6)

Trade name: CARAMBA Profi High performance special-purpose remover (Aerosol)





(Contd. of page 5)

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.


14 Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· IMDG	AEROSOLS (Kohlenwasserstoffe, Flüssig (Isoheptan u. Cycloheptan), DIPENTENE), MARINE POLLUTANT
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2 5F Gases.
· Label	2.1
· IMDG	
	
· Class	2.1
· Label	2.1

(Contd. on page 7)

Trade name: CARAMBA Profi High performance special-purpose remover (Aerosol)

(Contd. of page 6)

· IATA	
	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: (R)-p-mentha-1,8-diene
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ):	E0
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to EU guidelines:
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- Code letter and hazard designation of product:



Xi Irritant
F+ Extremely flammable
N Dangerous for the environment

- Hazard-determining components of labelling:
(R)-p-mentha-1,8-diene
- Risk phrases:
 - 12 Extremely flammable.
 - 43 May cause sensitisation by skin contact.
 - 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - 67 Vapours may cause drowsiness and dizziness.
- Safety phrases:
 - 2 Keep out of the reach of children.
 - 16 Keep away from sources of ignition - No smoking.
 - 23 Do not breathe spray.
 - 24 Avoid contact with skin.
 - 51 Use only in well-ventilated areas.

(Contd. on page 8)

Trade name: CARAMBA Profi High performance special-purpose remover (Aerosol)

(Contd. of page 7)

60 This material and its container must be disposed of as hazardous waste.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

· **Classification in accordance with Directive 75/324/EEC:** Extremely flammable

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· *** Data compared to the previous version altered.**
