



# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 29/06/2023 Revision date: 28/06/2023 Supersedes version of: 24/01/2023 Version: 2.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Inox Kleen  
UFI : P9KX-P8GC-A00K-F5GP  
Product code : BDS002536AE  
Type of product : Detergent  
Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Use of the substance/mixture : Cleaners - Heavy duty

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

CRC Industries Europe B.V.  
Touwslagerstraat 1  
9240 Zele  
Belgium  
T +32(0)52/45.60.11 - F +32(0)52/45.00.34  
[hse@crcind.com](mailto:hse@crcind.com) - [www.crcind.com](http://www.crcind.com)

#### 1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11  
Office hours: 9-17h CET

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 3 H229  
Serious eye damage/eye irritation, Category 2 H319  
Aspiration hazard, Category 1 H304  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Causes serious eye irritation. May be fatal if swallowed and enters airways.

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H229 - Pressurised container: May burst if heated.  
H319 - Causes serious eye irritation.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251 - Do not pierce or burn, even after use.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

EUH-statements

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
EUH208 - Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5). May produce an allergic reaction.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Other information

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 926-141-6 REACH-no: 01-2119456620-43	10 – 25	Asp. Tox. 1, H304 EUH066
White mineral oil (petroleum) substance with national workplace exposure limit(s) (BE)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 01-2119487078-27	10 – 25	Not classified
propane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	1 – 5	Flam. Gas 1, H220 Press. Gas (Liq.), H280
isobutane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	1 – 5	Flam. Gas 1, H220 Press. Gas (Liq.), H280

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	1 – 5	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Decan-1-ol, ethoxylated	CAS-No.: 26183-52-8 EC-No.: 500-046-6	1 – 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Dam. 1, H318
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	< 0,005	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 2 (Inhalation:dust,mist), H330 (ATE=0,05 mg/l/4h) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	( 0,05 ≤C ≤ 100) Skin Sens. 1, H317

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

- Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear appropriate protective equipment and clothing during clean-up.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

propane (74-98-6)	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
isobutane (75-28-5)	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan
OEL STEL	2370 mg/m <sup>3</sup>
OEL STEL [ppm]	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
butane (106-97-8)	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan
OEL STEL	2370 mg/m <sup>3</sup>
OEL STEL [ppm]	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
White mineral oil (petroleum) (8042-47-5)	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Huiles minérales (brouillards) # Olie (minerale-; nevel)
OEL TWA	5 mg/m <sup>3</sup>
OEL STEL	10 mg/m <sup>3</sup>
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

Decan-1-ol, ethoxylated (26183-52-8)	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	2080 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	294 mg/m <sup>3</sup>

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Decan-1-ol, ethoxylated (26183-52-8)</b>	
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	87 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	1250 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,292 mg/l
PNEC aqua (marine water)	0,0292 mg/l
PNEC aqua (intermittent, freshwater)	0,0039 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	31,92 mg/kg dwt
PNEC sediment (marine water)	3,19 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	1 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	1,4 mg/l
<b>1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0,966 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	6,81 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, inhalation	1,2 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0,345 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	4,03 µg/l
PNEC aqua (marine water)	0,403 µg/l
PNEC aqua (intermittent, freshwater)	1,1 µg/l
PNEC aqua (intermittent, marine water)	110 ng/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	49,9 µg/kg dw
PNEC sediment (marine water)	4,99 µg/kg dw
<b>PNEC (Soil)</b>	
PNEC soil	3 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	1,03 mg/l

### 8.1.5. Control banding

No additional information available

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

###### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

##### 8.2.2.2. Skin protection

###### Skin and body protection:

Wear suitable protective clothing

###### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Neoprene gloves are recommended.

##### 8.2.2.3. Respiratory protection

###### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. ABEK

##### 8.2.2.4. Thermal hazards

###### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

#### 8.2.3. Environmental exposure controls

##### Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Propane/butane propelled liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

pH	: 9,79
Viscosity, kinematic	: < 20,5 mm <sup>2</sup> /s at 40 °C
Solubility	: soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,955 g/cm <sup>3</sup> at 20 °C
Relative density	: 0,955 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 25 – 50 %

#### 9.2.2. Other safety characteristics

VOC content : 152 g/l  
Additional information : For aerosols data for the product without propellant.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity (oral)** : Not classified (Based on available data, the classification criteria are not met)  
**Acute toxicity (dermal)** : Not classified (Based on available data, the classification criteria are not met)  
**Acute toxicity (inhalation)** : Not classified (Based on available data, the classification criteria are not met)

#### Decan-1-ol, ethoxylated (26183-52-8)

LD50 dermal rabbit	> 3000 mg/kg bodyweight
--------------------	-------------------------

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LD50 oral	> 5000 mg/kg bodyweight
-----------	-------------------------

LD50 dermal rat	> 2000 mg/kg bodyweight
-----------------	-------------------------

LC50 Inhalation - Rat (Dust/Mist)	> 4950 mg/l
-----------------------------------	-------------



# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>White mineral oil (petroleum) (8042-47-5)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5 mg/l/4h
<b>1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l/4h
<b>Skin corrosion/irritation</b>	: Not classified (Based on available data, the classification criteria are not met) pH: 9,79
<b>1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)</b>	
pH	5,5 – 8,5
<b>Serious eye damage/irritation</b>	: Causes serious eye irritation. pH: 9,79
<b>1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)</b>	
pH	5,5 – 8,5
<b>Respiratory or skin sensitisation</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Germ cell mutagenicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Carcinogenicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Reproductive toxicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)</b>	
NOAEL (animal/female, F0/P)	112 mg/kg bodyweight
NOAEL (animal/female, F1)	56,6 mg/kg bodyweight
<b>STOT-single exposure</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>STOT-repeated exposure</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Aspiration hazard</b>	: May be fatal if swallowed and enters airways.
<b>Inox Kleen</b>	
Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm <sup>2</sup> /s at 40 °C
<b>Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b>	
Viscosity, kinematic	2,4 mm <sup>2</sup> /s at 20 °C
<b>White mineral oil (petroleum) (8042-47-5)</b>	
Viscosity, kinematic	> 25 mm <sup>2</sup> /s

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### 11.2.2. Other information

No additional information available

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LC50 - Fish [1]	> 1000 mg/l
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 1000 mg/l

#### White mineral oil (petroleum) (8042-47-5)

LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
NOEC chronic fish	> 1000 mg/l

#### 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

LC50 - Fish [1]	2,2 mg/l
EC50 - Crustacea [1]	3,27 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	0,11 mg/l
NOEC chronic fish	0,21 mg/l 28 d
NOEC chronic crustacea	1,2 mg/l 21 d

#### 12.2. Persistence and degradability

##### Inox Kleen

Persistence and degradability	Not established. No data is available on the degradability of this product.
-------------------------------	---

#### 12.3. Bioaccumulative potential

##### Inox Kleen

Partition coefficient n-octanol/water (Log Kow)	Not applicable
---	----------------

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Partition coefficient n-octanol/water (Log Pow)	> 3
---	-----

#### 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

Partition coefficient n-octanol/water (Log Pow)	0,7
---	-----

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

##### Inox Kleen

Results of PBT assessment	Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII
---------------------------	---

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

Additional information : No other effects known  
Global warming potential (GWP) : 0 (Fluorinated greenhouse gases - (EC) No 517/2014)






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW) code : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, non-flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.2, (E)	UN 1950 AEROSOLS, 2.2	UN 1950 Aerosols, non-flammable, 2.2	UN 1950 AEROSOLS, 2.2	UN 1950 AEROSOLS, 2.2
<b>14.3. Transport hazard class(es)</b>				
2.2	2.2	2.2	2.2	2.2
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 5A  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 1I

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Tunnel restriction code (ADR)	: E

### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A98, A145, A167, A802
ERG code (IATA)	: 2L

### Inland waterway transport

Classification code (ADN)	: 5A
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP
Ventilation (ADN)	: VE04
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: 5A
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 20

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

###### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

###### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

###### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

###### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

###### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

###### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

###### VOC Directive (2004/42)

VOC content : 152 g/l

###### Detergent Regulation (648/2004)

Labelling of contents	
Component	%
aliphatic hydrocarbons	15-30%
non-ionic surfactants	<5%
BENZISOTHIAZOLINONE	

###### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

###### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

##### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

#### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Abbreviations and acronyms:

COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

### Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 3	Aerosol, Category 3
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.

# Inox Kleen

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Full text of H- and EUH-statements:

EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5). May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
H220	Extremely flammable gas.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.