

800988

823807

PROXXON

Ihr Gerät funktioniert nicht ordentlich? Dann bitte die Bedienungsanleitung noch einmal genau durchlesen. Ist es tatsächlich defekt, senden Sie es bitte an:

**Proxxon Zentralservice
D-54518 Niersbach**


**Proxxon Zentralservice
A-4224 Wartberg / Aist**

Wir reagieren prompt und zuverlässig! Über diese Adresse können Sie auch alle erforderlichen Ersatzteile bestellen.

Wichtig: Eine kurze Fehlerbeschreibung hilft uns, noch schneller zu reagieren. Bei Rücksendungen innerhalb der Garantiezeit bitte Kaufbeleg beifügen.

PROXXON

NETZGERÄT NG 2/S UND NG 2/E



Manual

(D)

(GB)

(F)

(I)

(E)


(NL)

(DK)

(S)

(CZ)

(TR)



GB PROXXON - POWER
SUPPLY UNITS - NG 2/S
AND NG 2/E

Description

The NG 2/S and NG 2/E Power Supply Units provide a safe power source for all PROXXON -devices requiring 12 Volt d.c. PROXXON-Power Supply Units have been developed to work efficiently and are built strictly in accordance with the VDE- safety regulations: (German Electrical Engineering Association)

- Compact construction, Noryl casing (particularly heat resistant)
- ports for instruments, hinged storage hooks
- Electronic overload protection (PTC)
- Thyristor regulated speed control (not applicable for NG 2/S)

Technical Details

Mains supply	230 V, 50-60 Hz
Off load voltage	16 V
Operational voltage	12 V (at 2 A)

Protection class II device



Overview

Legend (see diagram)

- 1 Socket for PROXXON-Electrical Appliance
- 2 LED display
- 3 Hooks for electrical tools
- 4 Ports for instruments
- 5 Control knob (not applicable for NG 2/S)

Safety Considerations

For your own safety please observe the following:

- Power Supply Units are only to be stored and used in dry rooms.
- Power Supply Units are to be kept out of children's reach.
- Remove the mains plug before cleaning the Power Supply Unit.
- Keep the mains power cable away from the working area.
- Check the power cable regularly. If it is damaged, it must be replaced at an authorized service center.
- Power Supply Units are to be opened only by authorized service personnel.
- If the Power Supply Unit cuts out due to overloading, then immediately switch off the electrical device which is attached (danger of uncontrolled running).
- Switch of the Power Supply Unit after use.
- Do not use the Power Supply Unit for purposes other than intended.
- Do not use the Power Supply Unit in the vicinity of inflammable gases or liquids.

Instructions for Use

1. Ensure that the electrical appliance is switched off before connecting to the Power Supply Unit.

Important!

Take the necessary safety precautions to prevent uncontrolled start up of the electrical appliance when connecting the Power Supply Unit (e.g., hold the appliance securely)

2. Mains connected. Red LED lamp 2 indicates standby.
3. Connect the electrical appliance to the Power Supply Unit. Socket 1 has a safety mechanism preventing damage if it were to be poled incorrectly.
4. Disconnect from mains after use.

Note:

Electrical appliances should not be used continuously for more than 15 minutes. If overloaded the Power Supply Unit will switch off automatically. If this occurs, switch off the Power Supply Unit (disconnect from mains). Leave to cool down for approximately 3 to 5 minutes after which the Power Supply Unit is ready for use again. See points 1-4 above.

Speed Control

The NG 2/E Power Supply Unit has a speed control feature via the control knob 5. Turning it anticlockwise to the stop = slowest speed. Turning it clockwise to the stop = fastest speed.

If the electrical device begins to stall / stutter during slow speed operation, either increase the speed slightly or increase the load on the device: The thyristor control functions more effectively at higher current levels.

If using the NG 2/E Power Supply Unit with an electrical appliance, which likewise is thyristor regulated, it must be set to maximum. The correct speed should then be set on the electrical appliance itself.

Disposal:

Please do not dispose off the machine!



Please do not dispose of the device in domestic waste! The device contains valuable substances that can be recycled. If you have any questions about this, please contact your local waste management enterprise or other corresponding municipal facilities.

EC Declaration of Conformity

We declare and assume sole responsibility for ensuring that this Product corresponds with the following EC guidelines:

- EC-EMI guideline 89/336
- EC-Low Voltage guideline 73/23
- EC-Machine guideline 89/392

M. Faßbender

Dipl. Ing. Martin Faßbender
(Chartered Engineer)

PROXXON S.A.
Department for Equipment Safety

Stand: September '97