

Page 1/13

Revision: 02.04.2017

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017

Version number 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BRUNOX® epoxy (BULK)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC9a Coatings and paints, thinners, paint removers

PC14 Metal surface treatment products

· Process category

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· Application of the substance / the mixture Coating material

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

BRUNOX Korrosionsschutz GmbH Adlzreiterstrasse 13, 85051 Ingolstadt Postfach 100127, 85001 Ingolstadt

Tel. + 49/ (0) 841 961 29 04 Fax + 49/ (0) 841 961 29 13

E-mail: office@brunox.com

www.brunox.com

BRUNOX AG

Tunnelstrasse 6

CH - 8732 Neuhaus/SG

Tel. +41/ (0)55 285 80 80 Fax +41/ (0)55 285 80 81

E-mail: office@brunox.com

www.brunox.swiss

· Further information obtainable from: Abteilung Produktsicherheit: Tel. +41/ (0)79 372 34 44

(Contd. on page 2)



Page 2/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 1)

· 1.4 Emergency telephone number:

Toxikologisches Informationszentrum CH - 8030 Zürich, Freiestrasse 16

Tel. +41/ 044 251 51 51

Notruf - CH, STIZ : 145 Notruf - D - : Giftnotrufzentrale 030 19240 Notruf - BE - : 070 -245 245 EUROPÄISCHE NOTRUFNR. : 112

Notruf - GB -: 844 892 0111

Notruf - IE - : + 353 1 837 9964 (medical professionals); + 353 1 809 2166 (public)

Notruf - IS -: + 354 543 22 22

Notruf - JP - : + 81 72 727 2499; + 81 29 852 9999

Notruf - NZ -: 0800 764 766

Notruf - PK -: + 92 21 9920509; + 92 21 35686535

Notruf - PH -: +632 524 10 78; +632 544 84 00; local 2311

Notruf - SA -: +966 146 77 353, +966 3 8155 646; Ext. 280, 282, 283

Notruf - TH - : + 66 201 1086 Notruf - UAE - : 800 424 Notruf - ZA - : + 27 824 910 160

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.



Page 3/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 2)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

<u>PBT</u>: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-XXXX CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-XXXX CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44-XXXX CAS: 64-18-6 EINECS: 200-579-1 Reg.nr.: 01-2119491174-37-XXXX CAS: 64-18-6 EINECS: 200-579-1 Reg.nr.: 01-2119491174-37-XXXX Reg.nr.: 01-2119491174-37-XXXX Symbol Standard St	zangereae compensation		
CAS: 108-65-6 2-methoxy-1-methylethyl acetate 10-25% EINECS: 203-603-9	EINECS: 203-539-1	♠ Flam. Liq. 3, H226	10-25%
EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-XXXX	CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate	10-25%
EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX Eye Irrit. 2, H319; STOT SE 3, H336 CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44-XXXX CAS: 64-18-6 EINECS: 200-579-1 Reg.nr.: 01-2119491174-37-XXXX Skin Corr. 1C, H314	EINECS: 200-661-7	Flam. Lig. 2, H225	2.5-<10%
EINECS: 203-961-6 Reg.nr.: 01-2119475104-44-XXXX CAS: 64-18-6 EINECS: 200-579-1 Reg.nr.: 01-2119491174-37-XXXX Skin Corr. 1C, H314	EINECS: 200-662-2	♠ Flam. Lig. 2. H225	2.5-<10%
EINECS: 200-579-1	EINECS: 203-961-6	_ `	2.5-<10%
	EINECS: 200-579-1	Acute Tox. 3, H331 Skin Corr. 1C, H314	2.5-<10%

(Contd. on page 4)



Page 4/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 3)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Position and transport stably in side position.

Seek medical treatment.

· After inhalation:

Take affected persons into fresh air and keep quiet.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

A person vomiting while laying on their back should be turned onto their side.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

GB



Page 5/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 4)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Mount respiratory protective device.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

· Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 6)



Page 6/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 5)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 107-98-2 1-methoxy-2-propanol

WEL (Great Britain) Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Sk

WES (Australia) Short-term value: 553 mg/m³, 150 ppm

Long-term value: 369 mg/m³, 100 ppm

WES (New Zealand) Short-term value: 553 mg/m³, 150 ppm

Long-term value: 369 mg/m³, 100 ppm

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain) Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

WES (Australia) Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

CAS: 67-63-0 propan-2-ol

WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

WES (Australia) Short-term value: 1230 mg/m³, 500 ppm

Long-term value: 983 mg/m³, 400 ppm

WES (New Zealand) Short-term value: 1230 mg/m³, 500 ppm

Long-term value: 983 mg/m³, 400 ppm

CAS: 67-64-1 acetone

WEL (Great Britain) Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

WES (Australia) Short-term value: 2375 mg/m³, 1000 ppm

Long-term value: 1185 mg/m³, 500 ppm

WES (New Zealand) Short-term value: 2375 mg/m³, 1000 ppm

Long-term value: 1185 mg/m³, 500 ppm

bio

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

WEL (Great Britain) Short-term value: 101.2 mg/m³, 15 ppm

Long-term value: 67.5 mg/m³, 10 ppm

(Contd. on page 7)



Page 7/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 6)

CAS: 64-18-6 formic acid

WEL (Great Britain) Long-term value: 9.6 mg/m³, 5 ppm WES (Australia) Short-term value: 19 mg/m³, 10 ppm

Long-term value: 9.4 mg/m³, 5 ppm

WES (New Zealand) Short-term value: 19 mg/m³, 10 ppm

Long-term value: 9.4 mg/m³, 5 ppm

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A/P2

Filter AX

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check the permeability prior to each anewed use of the glove.

· Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)



Page 8/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 7)

· Eye protection:



Tightly sealed goggles

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

· Appearance:

Form: Fluid

Colour: Amber coloured · Odour: Characteristic · Odour threshold: Not determined.

· pH-value at 20 °C (68 °F): 3.9

· Change in condition

Melting point/freezing point: Initial boiling point and boiling range: 82 °C (180 °F) 13 °C (55 °F) · Flash point: · Flammability (solid, gas): Not applicable. 225 °C (437 °F) · Ignition temperature: · Decomposition temperature: Not determined.

Product is not selfigniting. Auto-ignition temperature:

Product is not explosive. However, formation of · Explosive properties:

Undetermined.

explosive air/vapour mixtures are possible.

· Explosion limits:

1.5 Vol % Lower: Upper: 20.0 Vol %

· Vapour pressure at 20 °C (68 °F): 12 hPa (9 mm Hg)

0.99 +/- 0.02 g/cm3 (8.262 +/- 0.167 lbs/gal) Density at 20 °C (68 °F):

· Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not determined.

· Solubility in / Miscibility with

Not miscible or difficult to mix. water:

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 9)



Page 9/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 8)

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

 Organic solvents:
 45.9 %

 VOC (EC)
 45.90 %

 Solids content:
 1.5 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability stable
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Forms explosive gas mixture with air.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information:

As long as the prescribed application concentrations are maintained there is no danger that stable emulsions will form.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 36789 mg/kg (rat)

Inhalative LC50/4 h 30.5 mg/l

CAS: 107-98-2 1-methoxy-2-propanol

Oral LD50 5660 mg/kg (rat)
Dermal LD50 13000 mg/kg (rabbit)

Inhalative LC50/4 h 6 mg/l (rat)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8532 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

(Contd. on page 10)



Page 10/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 9)

CAS: 67-63-0 propan-2-ol

Oral LD50 5045 mg/kg (rat)
Dermal LD50 12800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

CAS: 67-64-1 acetone

 Oral
 LD50
 5800 mg/kg (rat)

 Dermal
 LD50
 20000 mg/kg (rabbit)

 CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

Oral LD50 5660 mg/kg (rat)

Dermal LD50 4000 mg/kg (rabbit)

CAS: 64-18-6 formic acid

Oral LD50 1100 mg/kg (rat) Inhalative LC50/4 h 3 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 11)



Page 11/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 10)

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP 3 Flammable

HP 4 Irritant - skin irritation and eye damage

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR/RID/ADN, IMDG, IATA UN1866

· 14.2 UN proper shipping name

· ADR/RID/ADN 1866 RESIN SOLUTION, special provision 640D

· IMDG, IATA RESIN SOLUTION

· 14.3 Transport hazard class(es)

· ADR/RID/ADN, IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR/RID/ADN, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 33 EMS Number: F-E,S-E

· Stowage Category B

(Contd. on page 12)



Page 12/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 11)

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR/RID/ADN

Limited quantities (LQ)
 Excepted quantities (EQ)
 5L
 Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

• Transport category 2 • Tunnel restriction code D/E

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 5L
 Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1866 RESIN SOLUTION, SPECIAL

PROVISION 640D, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 55
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

(Contd. on page 13)



Page 13/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2017 Version number 5 Revision: 02.04.2017

Trade name: BRUNOX® epoxy (BULK)

(Contd. of page 12)

H336 May cause drowsiness or dizziness.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

· * Data compared to the previous version altered.

GB