Document: TEB branch muff

U.I. Lapp GmbH

TEB branch muff

DATASHEET

TEB branch muffs with adhesive coating inside can be used for insulating and sealing of cable splices.







Good chemical resistance



Halogen-free



UV-resistant



Waterproof

Application range Insulation and sealing of cable splices

Benefits

Secure sealing through thermoplastic adhesive coating on the inside Good resistance to chemicals and solvents Ensures high tensile strength and mechanical protection

Design Double-walled

Norm references / Approvals

Protection rating: IP67

Remark

1. after shrinking +/- 10%; 2. after shrinking +/- 20% Photographs are not to scale and do not represent detailed images of the respective products.



1/3

61830150 14.11.2013 **TEB branch muff**



61830150

14.11.2013

Technical Data

Article description:	TEB4-55/20
Number of cores:	4
H max. mm:	55
H min. mm:	22
K max. mm:	20
K min. mm:	8.5
P* mm:	190
R* mm:	45
Pieces / PU:	1
General:	UV-resistant
Info:	Shrinking ratio: > 2:1
Colour delivered:	Black
Material:	Cross-linked modified polyolefin, with thermoplastic adhesive coating inside Halogen-free and silicone-free
Temperature range:	-55°C to +100 °C Shrinking temperature: +120°C

Product Management	Document: TEB branch muff	2/3
PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved Photographs are not to scale and do not represent detailed images of the respective products.		


U.I. Lapp	
GmbH	

DATASHEET



TEB branch muff

61830150 14.11.2013



Product Management	Document: TEB branch muff	3 / 3
PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved Photographs are not to scale and do not represent detailed images of the respective products.		