Document: TEC sealing cap

TEC sealing cap

DATASHEET

TEC sealing caps with adhesive coating inside can be used for insulating and sealing of cable splices.



U.I. Lapp

GmbH



Good chemical resistance



Halogen-free



UV-resistant



Waterproof

Application range

For sealing cable ends against the seepage of moisture and contaminants

Benefits

Secure sealing through thermoplastic adhesive coating on the inside Good resistance to chemicals and solvents Ensures high tensile strength and mechanical protection

Norm references / Approvals

Product Management

Protection rating: IP67

Remark

1. after shrinking +/- 10%; 2. after shrinking +/- 20% Photographs are not to scale and do not represent detailed images of the respective products.



1/3

61830010 14.11.2013

U.I. Lapp GmbH		DATASHEET		
		TEC sealing cap	61830010 14.11.2013	
Technical D Article descrip		TEC 25	9	
H max. mm:		25	25	
H min. mm:		9	9	
J max. mm:		6.5	6.5	
Cable Ø (mm):		10 - 22	10 - 22	
R* after shrinking (mm):		50	50	
Panel thickness HW* (mm):		2.3	2.3	
Pieces / PU:		10	10	
General:			UV-resistant Double-walled	
Colour delivered:		Black	Black	
Material:		coating	Cross-linked modified polyolefin, with thermoplastic adhesive coating inside Halogen-free and silicone-free	
Temperature range:			-55°C to +100 °C Shrink temperature: 135°C	

Product Management	Document: TEC sealing cap	2/3
N 0486/01_03.10 hotographs are not to scale and do not represent		

U.I. Lapp GmbH	DATASHEET	
	TEC sealing cap	61830010 14.11.2013



Product Management	Document: TEC sealing cap	3 / 3
PN 0486/01_03.10 Photographs are not to scale and do not represent	©2012 Lapp Group - Technical changes reserved detailed images of the respective products.	