DATASHEET



Conductor end sleeves AH, not insulated

62120280 14.11.2013

Uninsulated/not-insulated conductor end sleeves for cabinet builders



Application range

Control cabinet wiring

Benefits Slightly funnel-shaped opening makes it easy to slip it onto the core

Norm references / Approvals

In accordance with DIN 46228

Note

For processing tools see the keyword index "crimping pliers for conductor end sleeves" Other sizes are available upon request

Remark

Other sizes are available upon request. Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Article designation:	AH DIN 16/12
For mm ² :	16
AWG:	6
l1 mm:	12
d 1 mm:	5.8
d 2 mm:	7.5
s mm:	0.2
Pieces / PU:	500
Material:	Tinned electrolyte copper
Temperature range:	max. +200°C

Τ



Т

Product Management	Document: Conductor end sleeves AH, not insulated	1 / 2
PN 0486/01_03.10 Photographs are not to scale and do not represent	©2012 Lapp Group - Technical changes reserved t detailed images of the respective products.	


U.I.	Lapp
Grr	ıbH

DATASHEET



Conductor end sleeves AH, not insulated

62120280 14.11.2013



Product Management	Document: Conductor end sleeves AH, not insulated	2/2
PN 0486/01 03.10	©2012 Lapp Group - Technical changes reserved	