# DATASHEET



### Conductor end sleeves insulated

61801830 14.11.2013

Conductor end sleeves with insulation for cabinet builders , according to DIN or German colour code, CSA approved, halogen-free





Halogen-free

#### Application range

Control cabinets and equipment wiring

#### **Benefits**

Funnel-shaped opening makes it easy to slip them onto the strands The conductor is permanently connected to the collar by crimping

#### Norm references / Approvals

All DIN conductor end-sleeves are in accordance with DIN 46228 Part 4 CSA approved, File-Number: LR 105629-1

#### Remark


K = short; N = medium; HL = large; L = extra large; Other sizes and colours are available upon request

Photographs are not to scale and do not represent detailed images of the respective products.

\*Under some circumstances the end sleeves withstand temperatures under -5°C. Please contact Lapp Kabel to clarify the specific application area.

#### **Technical Data**

Article designation:	AHI DIN N 10/12	
For mm <sup>2</sup> :	10	
AWG:	8	
Colour:	red	
l1 mm:	21	
l2 mm:	12	
d 1 mm:	4.6	
s1 mm:	0.2	
d 2 mm:	7.5	
s2 mm:	0.3	
Pieces / PU:	100	
Note:	Halogen-free	
Material:	Copper/PP Surface: tin-plated	
Temperature range:	-5°C to +105°C*	



U.I. Lapp	
GmbH	

## DATASHEET



Conductor end sleeves insulated

61801830 14.11.2013

Product Management	Document: Conductor end sleeves insulated	2/2
N 0486 /01 03 10	©2012 Lann Group - Technical changes reserved	