U.I. Lapp GmbH DATASHEET Conductor end sleeves insulated 61721990 14.11.2013

Conductor end sleeves with insulation for cabinet builders, according to DIN or German colour code, CSA approved, halogen-free









Halogen-free

Application range

Control cabinets and equipment wiring

Benefits

Funnel-shaped opening makes it easy to slip them onto the strands The conductor is permanently connected to the collar by crimping

Norm references / Approvals

All DIN conductor end-sleeves are in accordance with DIN 46228 Part 4 CSA approved, File-Number: LR 105629-1

Remark

K = short; N = medium; HL = large; L = extra large; Other sizes and colours are available upon request Photographs are not to scale and do not represent detailed images of the respective products.

*Under some circumstances the end sleeves withstand temperatures under -5°C. Please contact Lapp Kabel to clarify the specific application area.

Technical Data

Article designation: AHI L 16/18 For mm²: 16 AWG: 6 Colour: green I1 mm: 29 I2 mm: 18 d 1 mm: 6 s1 mm: 0.2 8.8 d 2 mm: s2 mm: 0.4 Pieces / PU: 100 Note: Halogen-free Material: Copper/PP


Temperature range: $-5^{\circ}\text{C to } +105^{\circ}\text{C}^{*}$



Product Management Document: Conductor end sleeves insulated	1 / 2
--	-------

Surface: tin-plated

U.I. Lapp GmbH	DATASHEET	LAPP GROUP
	Conductor and alcoves insulated	61721990
	Conductor end sleeves insulated	14.11.2013



Product Management	Document: Conductor end sleeves insulated	2/2	
--------------------	---	-----	--