U.I. Lapp GmbH DATASHEET Conductor end sleeves insulated 61721940 14.11.2013

Conductor end sleeves with insulation for cabinet builders, according to DIN or German colour code, CSA approved, halogen-free









Halogen-free

Application range

Control cabinets and equipment wiring

Benefits

Funnel-shaped opening makes it easy to slip them onto the strands The conductor is permanently connected to the collar by crimping

Norm references / Approvals

All DIN conductor end-sleeves are in accordance with DIN 46228 Part 4 CSA approved, File-Number: LR 105629-1

Remark

K = short; N = medium; HL = large; L = extra large; Other sizes and colours are available upon request Photographs are not to scale and do not represent detailed images of the respective products.

*Under some circumstances the end sleeves withstand temperatures under -5°C. Please contact Lapp Kabel to clarify the specific application area.

Technical Data

i common bata	
Article designation:	AHI N 6/12
For mm ² :	6
AWG:	10
Colour:	black
I1 mm:	20
I2 mm:	12
d 1 mm:	3.6
s1 mm:	0.2
d 2 mm:	6.2
s2 mm:	0.3
Pieces / PU:	100
Note:	Halogen-fre

Note: Halogen-free


Material: Copper/PP
Surface: tip pl

Surface: tin-plated

Temperature range: -5°C to +105°C*

Product Management Document: Conductor end sleeves insulated	1/2
--	-----

U.I. Lapp GmbH	DATASHEET	LAPP GROUP
	Conductor end sleeves insulated	61721940 14.11.2013



Product Management	Document: Conductor end sleeves insulated	2/2
--------------------	---	-----