

U.I. Lapp GmbH	<h1>DATASHEET</h1>	
	Conductor end sleeves XL, insulated	61802066 14.11.2013

Insulated conductor end sleeves particular for UL (MTW)-CSA-HAR multi-standard single cores, funnel-shaped insulation sleeve opening



Halogen-free

Info

Suitable conductor end sleeves for UL(MTW)-CSA-HAR multi-standard single cores

Application range

Suitable conductor end sleeves for UL(MTW)-CSA-HAR multi-standard single cores

Benefits

The specially produced conductor end sleeves with funnel-shaped insulation sleeve opening make it significantly easier to slip on the strands.

Design

Because of their approval for numerous markets, special conductor end sleeves with the cross sections listed below are needed for our multi-standard single cores.

The conductor is permanently connected to the collar by crimping

Norm references / Approvals

All DIN conductor end-sleeves are in accordance with DIN 46228 Part 4

Remark

Sleeves are available in 8 and 10 mm lengths, depending on the type of application.

Photographs are not to scale and do not represent detailed images of the respective products.



Product Management	Document: Conductor end sleeves XL, insulated	1 / 3
--------------------	---	-------

U.I. Lapp GmbH	DATASHEET	
	Conductor end sleeves XL, insulated	61802066 14.11.2013

Technical Data

Article designation:	Conductor end sleeves XL 1.0 RD 10
For mm ² :	1
AWG:	18
Colour:	red
l1 mm:	16
l2 mm:	10
d 1 mm:	1.5
s1 mm:	0.15
d 2 mm:	3.4
s2 mm:	0.3
Pieces / PU:	500
Approvals:	In accordance with DIN 46228
Note:	For processing tools see the keyword index "crimping pliers for conductor end sleeves"
Info:	Halogen-free and silicone-free
Material:	Sleeve made of tin-plated electrolytic copper Polypropylene plastic collar
Temperature range:	Permanent load -5°C up to +105°C, temporary load +120°C

Product Management	Document: Conductor end sleeves XL, insulated	2 / 3
--------------------	---	-------

U.I. Lapp GmbH	<h1>DATASHEET</h1>	 LAPP GROUP
	Conductor end sleeves XL, insulated	61802066 14.11.2013



Product Management	Document: Conductor end sleeves XL, insulated	3 / 3
--------------------	---	-------