
U.I. Lapp GmbH	DATASHEET	LAPP GROUP
	Insulated cable lugs	63112010
		14.11.2013

Insulated cable lugs Easy-Entry (ring cable lugs, (narrow) fork cable lugs, flange fork cable lugs, pin cable lugs, circular connector, connector sleeve butt connector, end joint)







Halogen-free

Application range

Manufacturing of control cabinets and equipment

Benefits

EASY-ENTRY funnel shape of the plastic sleeve enables simple, fast and safe insertion of the conductor No risk of bent and crushed cables
For good strength and improved current conduction

Design

1 = ring cable lugs2 = forked cable lugs3 = pin cable lugs4 = circular connector5 = connector sleeve6 = butt connector7 = end connector

Norm references / Approvals

Tested in accordance with DIN IEC 60352 File Number E334109, see table

Note

For processing tools see the keyword index "crimping pliers for conductor end sleeves"

Product features

Hard-soldered cable lug that can be pressed in any position
For first-class connection with simple operating principle
Electrolytic tinning for max. corrosion protection
Flat receptacle material in contact pressing is double-folded and hard-soldered
Metal sleeves with internal corrugation

Remark

Other sizes and colours are available upon request.

Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: Insulated cable lugs	1/3
--------------------	--------------------------------	-----

Technical Data

Article designation: L-RBJ For mm 2 : 1,5 - 2,5 UL approval: no

Core colour: transparent

Pieces / PU: 100

General: Other sizes and colours (also DIN) are available upon request

Halogen-free

Note: For processing tools see the keyword index "crimping pliers for

other connections"

Material: High-quality electrolytic copper for good conductivity

Polyamide insulation

Temperature range: -40°C to +105°C

Short-term: up to +120°C

U.I. Lapp GmbH	DATASHEET	LAPP GROUP
	Insulated cable lugs	63112010
		14.11.2013



Product Management Document: Insulate	d cable lugs 3 / 3
---------------------------------------	--------------------