


| | | |
|-------------------|-----------------------------|--|
| U.I. Lapp GmbH | DATASHEET |  |
| | Insulated cable lugs | 63112020 14.11.2013 |

Insulated cable lugs Easy-Entry (ring cable lugs, (narrow) fork cable lugs, flange fork cable lugs, pin cable lugs, circular connector, connector sleeve butt connector, end joint)



Halogen-free

Application range

Manufacturing of control cabinets and equipment

Benefits

EASY-ENTRY funnel shape of the plastic sleeve enables simple, fast and safe insertion of the conductor
No risk of bent and crushed cables
For good strength and improved current conduction

Design

1 = ring cable lugs 2 = forked cable lugs 3 = pin cable lugs 4 = circular connector 5 = connector sleeve 6 = butt connector 7 = end connector

Norm references / Approvals

Tested in accordance with DIN IEC 60352
File Number E334109, see table

Note

For processing tools see the keyword index "crimping pliers for conductor end sleeves"

Product features

Hard-soldered cable lug that can be pressed in any position
For first-class connection with simple operating principle
Electrolytic tinning for max. corrosion protection
Flat receptacle material in contact pressing is double-folded and hard-soldered
Metal sleeves with internal corrugation

Remark

Other sizes and colours are available upon request.
Photographs are not to scale and do not represent detailed images of the respective products.

| | | |
|--------------------|--------------------------------|-------|
| Product Management | Document: Insulated cable lugs | 1 / 3 |
|--------------------|--------------------------------|-------|

| | | |
|-------------------|-----------------------------|--|
| U.I. Lapp GmbH | DATASHEET |  LAPP GROUP |
| | Insulated cable lugs | 63112020 14.11.2013 |

Technical Data

| | |
|-----------------------|--|
| Article designation: | L-RCJ |
| For mm ² : | 4 - 6 |
| UL approval: | no |
| Core colour: | yellow |
| Pieces / PU: | 100 |
| General: | Other sizes and colours (also DIN) are available upon request Halogen-free |
| Note: | For processing tools see the keyword index "crimping pliers for other connections" |
| Material: | High-quality electrolytic copper for good conductivity Polyamide insulation |
| Temperature range: | -40°C to +105°C Short-term: up to +120°C |

| | | |
|--------------------|--------------------------------|-------|
| Product Management | Document: Insulated cable lugs | 2 / 3 |
|--------------------|--------------------------------|-------|

| | | |
|-------------------|-----------------------------|--|
| U.I. Lapp GmbH | <h1>DATASHEET</h1> |  LAPP GROUP |
| | Insulated cable lugs | 63112020 14.11.2013 |



| | | |
|--------------------|--------------------------------|-------|
| Product Management | Document: Insulated cable lugs | 3 / 3 |
|--------------------|--------------------------------|-------|