
U.I. Lapp GmbH	DATASHEET	LAPP GROUP
Ir	Inquisted apple luga	63104370
	Insulated cable lugs	14.11.2013

Insulated cable lugs Easy-Entry (ring cable lugs, (narrow) fork cable lugs, flange fork cable lugs, pin cable lugs, circular connector, connector sleeve butt connector, end joint)







Halogen-free

## Application range

Manufacturing of control cabinets and equipment

#### Benefits

EASY-ENTRY funnel shape of the plastic sleeve enables simple, fast and safe insertion of the conductor No risk of bent and crushed cables
For good strength and improved current conduction

#### Design

1 = ring cable lugs2 = forked cable lugs3 = pin cable lugs4 = circular connector5 = connector sleeve6 = butt connector7 = end connector

#### Norm references / Approvals

Tested in accordance with DIN IEC 60352 File Number E334109, see table

## Note

For processing tools see the keyword index "crimping pliers for conductor end sleeves"

# **Product features**

Hard-soldered cable lug that can be pressed in any position
For first-class connection with simple operating principle
Electrolytic tinning for max. corrosion protection
Flat receptacle material in contact pressing is double-folded and hard-soldered
Metal sleeves with internal corrugation

#### Remark

Other sizes and colours are available upon request.

Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: Insulated cable lugs	1/3
--------------------	--------------------------------	-----

U.I. Lapp GmbH	DATASHEET	<b>LAPP GROUP</b>
	Insulated cable lugs	63104370
		14.11.2013

**Technical Data** 

Article designation:

L-RC 8

For mm²:

4 - 6

UL approval:

Connection bolt:

M 8

Core colour:

Pieces / PU:

100

General: Other sizes and colours (also DIN) are available upon request

Halogen-free

Note: For processing tools see the keyword index "crimping pliers for

other connections"

Material: High-quality electrolytic copper for good conductivity

Polyamide insulation

Temperature range: -40°C to +105°C

Short-term: up to +120°C

U.I. Lapp GmbH	DATASHEET	<b>EXAPP GROUP</b>
	Insulated cable lugs	63104370
		14.11.2013



Product Management Document: Insulate	d cable lugs 3 / 3
---------------------------------------	--------------------