


U.I. Lapp GmbH	<b>DATASHEET</b>	
	<b>Insulated cable lugs</b>	<b>63104020</b> <b>14.11.2013</b>

Insulated cable lugs Easy-Entry (ring cable lugs, (narrow) fork cable lugs, flange fork cable lugs, pin cable lugs, circular connector, connector sleeve butt connector, end joint)



Halogen-free

### Application range

Manufacturing of control cabinets and equipment

### Benefits

EASY-ENTRY funnel shape of the plastic sleeve enables simple, fast and safe insertion of the conductor  
No risk of bent and crushed cables  
For good strength and improved current conduction

### Design

1 = ring cable lugs 2 = forked cable lugs 3 = pin cable lugs 4 = circular connector 5 = connector sleeve 6 = butt connector 7 = end connector

### Norm references / Approvals

Tested in accordance with DIN IEC 60352  
File Number E334109, see table

### Note

For processing tools see the keyword index "crimping pliers for conductor end sleeves"

### Product features

Hard-soldered cable lug that can be pressed in any position  
For first-class connection with simple operating principle  
Electrolytic tinning for max. corrosion protection  
Flat receptacle material in contact pressing is double-folded and hard-soldered  
Metal sleeves with internal corrugation

### Remark

Other sizes and colours are available upon request.  
Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: Insulated cable lugs	1 / 3
--------------------	--------------------------------	-------

U.I. Lapp GmbH	<b>DATASHEET</b>	
	<b>Insulated cable lugs</b>	<b>63104020</b> <b>14.11.2013</b>

### Technical Data

Article designation:	L-RZ 4
For mm <sup>2</sup> :	0,25 - 0,75
UL approval:	no
Connection bolt:	M 4
Core colour:	green
Pieces / PU:	100
General:	Other sizes and colours (also DIN) are available upon request Halogen-free
Note:	For processing tools see the keyword index "crimping pliers for other connections"
Material:	High-quality electrolytic copper for good conductivity Polyamide insulation
Temperature range:	-40°C to +105°C Short-term: up to +120°C

Product Management	Document: Insulated cable lugs	2 / 3
--------------------	--------------------------------	-------

U.I. Lapp GmbH	<b>DATASHEET</b>	 <b>LAPP GROUP</b>
	<b>Insulated cable lugs</b>	<b>63104020</b> <b>14.11.2013</b>



Product Management	Document: Insulated cable lugs	3 / 3
--------------------	--------------------------------	-------