Tube cable lugs KR/KRT/KRF, also for fine.wire copper conductors, class 2 and 5, tinned electrolyte copper, with inspection hole, for railway industry



Application range

KR: For fine and multi-wire copper conductors (class 2 an 5) with a cross-sectional range of 0.75 -10.00 mm²
KRT: For multi-wire copper conductors (class 2)with a cross-sectional range of 10 - 400 mm²
KRF: For fine wire copper conductors (class 2 and 5) with a cross-sectional range of 16 - 400 mm²
Mainly for connection to rails and to copper connectors
Max. 48 kW

Benefits

With inspection hole (from size 10 mm2 on, KR beginning 4 mm2)
High-quality electrolytic copper ensures a good crimping quality

Norm references / Approvals

In combination with recommended crimp tool fulfill requirments of SEN 245010, BS 4579:1, VDE 0220:1, EN-IEC 61238:1
UL file number: E205350 (see table)

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Article designation:	KRF 150/16
Screw hole Ø (mm):	16
UL approval:	yes
Length (mm):	80
Pressing dies:	B 25/13 B 25
d mm:	19
W mm:	36
Pieces / PU:	25
Material:	Tinned electrolyte copper
Temperature range:	Temperature range up to +90°C Working temperature: 110°C, max. +140°C

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.