

U.I. Lapp GmbH	DATASHEET	
	SILVYN® RILL PA 6	61746995 14.11.2013

Dimensionally stable
Flexible
High flame-retardance and self-extinguishing in accordance with UL 94V-0
Crush-resistant
Lightweight



Good chemical resistance



Flame-retardant



Halogen-free



Low weight



Reliability



Temperature-resistant




Variety of approval certifications




SILVYN®
KLICK-Y



SILVYN®
KLICK-GP/GM/
GPZ/GPZ-M



SILVYN®
KLICK 90°M/PG



SILVYN® KSE



SILVYN® KLICK-S
SILVYN® KLICK RH

Info

Maximum safety in the event of a fire

Application range

Mechanical engineering
Public utilities
Railway applications / vehicle construction
Moving applications
Outdoor application (in black)

Design

Fine-profile corrugated polyamide 6 conduit

Norm references / Approvals

UL FILENUMBER E308201

Note

UV and weather-resistant in black

Product Management	Document: SILVYN® RILL PA 6	1 / 3
--------------------	-----------------------------	-------

U.I. Lapp GmbH	DATASHEET	 LAPP GROUP
	SILVYN® RILL PA 6	61746995 14.11.2013

Product features

Halogen and cadmium-free

Abrasion-resistant

High resistance to oil, petrol, acids and other chemicals

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Article designation:	36
Article IØ x OØ (mm):	36 x 42,5
Bending radius (mm):	90
Suitable for SILVYN® KLICK-GM/90°M:	40 x 1,5
Suitable for SILVYN® KLICK-GP/90°PG:	36/ -
Suitable for SILVYN® KLICK-GPZ-M/GPZ:	50x1,5/36
PU ring (m):	25
Approvals:	UR File No. E308201 VDE EN/IEC 618386-23 DNV, Lloyd's Register Rail: DB DIN 5510 Teil2 (S4/SR2/ST2) SNCF NFF16-101/102 (I2/f2) UNDERGROUND BS 6853
Colour delivered:	Grey (RAL 7031) Black (RAL 9011), UV-resistant
Material:	PA 6 Silicone-free Halogen-free Fire behaviour according to UL 94V-0
Temperature range:	-40°C to +115°C short-term +150°C

Product Management	Document: SILVYN® RILL PA 6	2 / 3
--------------------	-----------------------------	-------

U.I. Lapp GmbH	DATASHEET	 LAPP GROUP
	SILVYN® RILL PA 6	61746995 14.11.2013



Product Management	Document: SILVYN® RILL PA 6	3 / 3
--------------------	-----------------------------	-------