

U.I. Lapp GmbH	DATASHEET	
	SKINDICHT® KU, KUS, KUK	51730110 14.11.2013

Enables the use of cable glands with smaller connection threads than the existing threaded holes
Glass fibre-reinforced for maximum mechanical stability



Space requirement

Application range

Machines
Devices
Housings

Design

PG connection thread

Design


SKINDICHT® KU with hexagon and flat design
SKINDICHT® KUS with hexagon and larger height
SKINDICHT® KUK with knurled heads

Remark

Photographs are not to scale and do not represent detailed images of the respective products.



Technical Data

Article designation / sizeOuter / inner:	KUK 36/29
Pieces / PU:	25
Colour delivered:	Light grey (RAL 7035)
Material:	Polyamide, glass fibre-reinforced
Temperature range:	KU, KUS: -40°C to +100°C KUK: -20°C to +80°C



Product Management	Document: SKINDICHT® KU, KUS, KUK	1 / 2
--------------------	-----------------------------------	-------

U.I. Lapp GmbH	DATASHEET	 LAPP GROUP
	SKINDICHT® KU, KUS, KUK	51730110 14.11.2013



Product Management	Document: SKINDICHT® KU, KUS, KUK	2 / 2
--------------------	-----------------------------------	-------