U.I. Lapp GmbH	DATASHEET	EAPP GROUP
	SKINDICHT® SR	52001060 14.11.2013

Reliable bending and anti-kink protection High strain relief Robust For cables with large outer diameters High degree of protection





Wide clamping range



Optimum strain relief



Robust

Application range

Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Handheld device
Portable equipment
Building sites
Moving machine parts

Design

PG connection thread

Note

Counter nut to be used: SKINDICHT® SM For EMC version, refer to SKINDICHT® SRE

Remark

Photographs are not to scale and do not represent detailed images of the respective products.



U.I. Lapp GmbH DATASHEET SKINDICHT® SR DATASHEET 52001060 14.11.2013

Technical Data

Article designation / size: SR 16/13 Clamping range ØF (mm): 11,5 - 13

Max. fitting size for installation (mm): 35
SW1/SW2 mm: 24 / 24
Overall length, C (mm): 67
Thread length, D (mm): 6.5
Pieces / PU: 25

Caution: The installation dimensions

can be found in appendix T21

On request: Available with long connection thread

Material: Body: nickel-plated brass

O-ring: NBR

Anti-kink protection: CR

Protection rating: IP 65

Temperature range: -20 °C to +80 °C

U.I. Lapp GmbH	DATASHEET	LAPP GROUP
	SKINDICHT® SR	52001060
		14.11.2013

