

Page 1 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.
STOT RE	2	H373-May cause damage to organs through prolonged
		an name at all arms arms but inhelation (as at all as much

or repeated exposure by inhalation (central nervous

system).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305



Danger

H317-May cause an allergic skin reaction. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (central nervous system).

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P280-Wear protective gloves. P314-Get medical advice/attention if you feel unwell.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents/container to special waste collection point.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

REGULATION (EC) No 648/2004

30 % and more aliphatic hydrocarbons less than 5 % aromatic hydrocarbons

perfumes

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

0.2 m.x.a. 0	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	(64742-48-9)
content %	40-60
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-	
25%)	
Registration number (REACH)	01-2119473977-17-XXXX
Index	



Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

EINECS, ELINCS, NLP	919-164-8 (REACH-IT List-No.)
CAS	
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
	Aquatic Chronic 3, H412
	STOT RE 1, H372 (central nervous system) (as inhalation)

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	307-593-8
CAS	97675-24-6
content %	1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317

Carbon dioxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	204-696-9
CAS	124-38-9
content %	1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

 $Wash\ thoroughly\ using\ copious\ water\ -\ remove\ contaminated\ clothing\ immediately.\ If\ skin\ irritation\ occurs\ (redness\ etc.),\ consult\ doctor.$

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media



Page 4 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

Suitable extinguishing media

Adapt to the nature and extent of fire. Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Oxides of sulphur Hydrocarbons

Toxic vapours

Danger of bursting (explosion) when heated

Explosive vapour/air mixture

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient ventilation.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities



(B)

Page 5 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

BMGV:

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Do not store with oxidizing agents.

Observe special regulations for aerosols!

Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons C	10-C13, n-alkanes, isoalkanes, cyclic	cs. < 2% aromatics	C	ontent %:40-60
WEL-TWA: 800 mg/m3	Trydrocarbono, C	WEL-STEL:	o, v 270 di omanoo		J. 10 10 00
Monitoring procedures:	_	Draeger - Hydrocarbons 2/a (81 03	581)		
3 / 3 / 3	-	Draeger - Hydrocarbons 0,1%/c (81			
	-	Compur - KITA-187 S (551 174)	,		
BMGV:			Other information: (V EH40)	VEL acc. to R	CP-method,
Chemical Name	Hydrocarbons, C	10-C13, n-alkanes, isoalkanes, cyclic	s. aromatics (2-25%)		Content %:1-5
WEL-TWA: 1000 mg/m3		WEL-STEL:	(= == ,=)		
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 03	581)		
01	=	Draeger - Hydrocarbons 0,1%/c (81			
	-	Compur - KITA-187 S (551 174)	,		
BMGV:		·	Other information: (V	VEL acc. to R	CP-method,
			EH40)		
Chemical Name	Carbon dioxide				Content %:1-2,5
WEL-TWA: 5000 ppm (9150 mg/m		WEL-STEL: 15000 ppm (27400) mg/m3) (WFL)		70.11 Z,0
ppm (9000 mg/m3) (EU)	10) (1122), 0000	1122 0122. 10000 pp.m (27 100	,g,) (** = =)		
Monitoring procedures:	_	Compur - KITA-126 B (549 475)			
Merine procedures.	_	Compur - KITA-126 SA (549 467)			
	_	Compur - KITA-126 SB (548 816)			
	_	Compur - KITA-126 SF (549 491)			
	_	Compur - KITA-126 SG (550 210)			
	_	Compur - KITA-126 SH (549 509)			
	_	Compur - KITA-126 UH (549 517)			
	_	Draeger - Carbon Dioxide 100/a (81	01.811)		
	_	Draeger - Carbon Dioxide 0,1%/a (C			
		Draeger - Carbon Dioxide 0,1 % (C	,		
	_	Draeger - Carbon Dioxide 0,3 /wa (C			
	-	Draeger - Carbon Dioxide 1 % a (CF			
	_	OSHA ID-172 (Carbon dioxide in wo		1000	
	-	NIOSH 6603 (Carbon dioxide) - 199		1990	
BMGV:		Triosi i odos (Carboli dioxide) - 199	Other information:	-	
			CCI IIIIOIIIIAGOII.		
Chemical Name	Oil mist, mineral				Content %:
WEL-TWA: 5 mg/m3 (ACGIH)		WEL-STEL: 10 mg/m3 (ACGIH	l)		
Monitoring procedures:	-	Draeger - Oil 10/a-P (67 28 371)			
DMOV	-	Draeger - Oil Mist 1/a (67 33 031)	00 16 1		
BMGV:			Other information:	•	
Chemical Name	Baseoil - unspeci	fied			Content %:
WEL-TWA: 300 mg/m3 (AGW)		WEL-STEL: 2(II) (AGW)			
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 03	581)	1	
	-	Draeger - Hydrocarbons 0,1%/c (81			
	_	Compur - KITA-187 S (551 174)	,		

Other information:



Page 6 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)								
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note		
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day			
Consumer	Human - dermal	Long term, systemic effects	DNEL	26	mg/kg bw/day			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	44	mg/kg bw/day			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	330	mg/m3			
Consumer	Human - inhalation	Long term, systemic effects	DNEL	71	mg/m3			

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.



Page 7 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol, Substance: Liquid

Colour: Brown, Clear
Odour: Characteristic
Odour threshold: Not determined
pH-value: Not determined
Melting point/freezing point: Not determined

Initial boiling point and boiling range:

Not determ
n.a.

Flash point: n.a.

Evaporation rate:

Flammability (solid, gas):

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Vapour density (air = 1):

Not determined

Not determined

Not determined

Not determined

Not determined

Density: 0,881 g/ml (20°C, Active substance)

Bulk density:

Solubility(ies):

Water solubility:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Not determined

Not determined

Not determined

Not determined

Viscosity: 17 mm2/s (40°C, Active substance)

Explosive properties: Not determined

Oxidising properties: No

9.2 Other information

Miscibility:

Rot determined Fat solubility / solvent:

Conductivity:

Not determined Ond determined Surface tension:

Not determined Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Pressure increase will result in danger of bursting.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.



Page 8 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011 Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t					
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t				0505 (0) (0) 0	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
A	1.050	0000		Б.	Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
A	1.050	5000	/ 0/0	Б.	Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8	Rat	OECD 403 (Acute	
01: " " "			h		Inhalation Toxicity)	B
Skin corrosion/irritation:						Repeated exposure may
						cause skin dryness or
					0505 405 44 4 5	cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant
B					Irritation/Corrosion)	N
Respiratory or skin sensitisation:					OECD 406 (Skin	Not sensitizising
					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative, Analogous
					Reverse Mutation Test)	conclusion
Carcinogenicity:					OECD 453 (Combined	Negative, Analogous
					Chronic	conclusion
					Toxicity/Carcinogenicity	
					Studies)	
Reproductive toxicity:					OECD 414 (Prenatal	Negative, Analogous
					Developmental	conclusion
					Toxicity Study)	
Reproductive toxicity:					OECD 421	Negative, Analogous
					(Reproduction/Develop	conclusion
					mental Toxicity	
					Screening Test)	
Specific target organ toxicity -						No indications of such an
single exposure (STOT-SE):						effect.



Page 9 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010 Valid from: 21.08.2015

PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL Art.: 3305

Specific target organ toxicity - repeated exposure (STOT-RE):		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Aspiration hazard:			Yes
Symptoms:			unconsciousness,
			headaches, dizziness

Toxicity / effect	Endpoin t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3400	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	13,1	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Maximum achievable concentration.
Skin corrosion/irritation:						Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizising
Germ cell mutagenicity:						Negative
Carcinogenicity:						Analogous conclusion, Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): central nervous system
Aspiration hazard:						Yes
Symptoms:						headaches, dizziness, fatigue, nausea
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): central nervous system

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts							
Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes	
	t						
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat			
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat			
Skin corrosion/irritation:				Rabbit		Not irritant	
Serious eye damage/irritation:				Rabbit		Not irritant	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative	
					Reverse Mutation Test)	_	

Carbon dioxide						
Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t					
Symptoms:						unconsciousness, blisters by skin-contact, vomiting, frostbite, annoyance, palpitations, itching, headaches, cramps, ear noises, dizziness

Endpoin	Value	Unit	Organism	Test method	Notes
t					
					Not irritant
					Not irritant
					Not sensitizising
	Endpoin t	Endpoin Value t	Endpoin Value Unit	Endpoin Value Unit Organism	Endpoin Value Unit Organism Test method t



Page 10 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

MULTI-SPRAY PLUS 7 500 mL Art.: 3305								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
Toxicity to fish:							n.d.a.	
Toxicity to daphnia:							n.d.a.	
Toxicity to algae:							n.d.a.	
Persistence and degradability:							Isolate as much as possible with an oil separator.	
Bioaccumulative potential:							n.d.a.	
Mobility in soil:							n.d.a.	
Results of PBT and vPvB assessment							n.d.a.	
Other adverse effects:							n.d.a.	

Hydrocarbons, C10-C	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,		
					mykiss	Acute Toxicity		
						Test)		
Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202		
						(Daphnia sp.		
						Acute		
						Immobilisation		
						Test)		
Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell	OECD 201		
					a subcapitata	(Alga, Growth		
						Inhibition Test)		
Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriell	OECD 201		
					a subcapitata	(Alga, Growth		
						Inhibition Test)		
Persistence and		28d	80	%		OECD 301 F		
degradability:						(Ready		
						Biodegradability -		
						Manometric		
						Respirometry		
						Test)		
Bioaccumulative	Log Pow		5,5-7,2					
potential:								
Mobility in soil:	Log Koc		>3					
Results of PBT and							No PBT substance, No	
vPvB assessment							vPvB substance	
Water solubility:			~10	mg/l			Slight	
Water solubility:							Insoluble	

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
Toxicity to fish:	LL50	96h	>10-	mg/l	Oncorhynchus	OECD 203 (Fish,		
			<100		mykiss	Acute Toxicity		
						Test)		
Toxicity to daphnia:	NOEC/NO	21d	0,097	mg/l	Daphnia magna	OECD 211		
	EL					(Daphnia magna		
						Reproduction		
						Test)		
Toxicity to daphnia:	EL50	48h	10-22	mg/l	Daphnia magna		Analogous conclusion	
Toxicity to algae:	EL50	72h	10-100	mg/l	Pseudokirchneriell	OECD 201		
					a subcapitata	(Alga, Growth		
						Inhibition Test)		



Page 11 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

Persistence and degradability:		28d	74,7	%	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) Readily biodegradable Readily biodegradable
Bioaccumulative potential:	Log Pow		4,2-7,2		
Bioaccumulative potential:	Log Kow		4,2-7,2		A notable biological accumulation potential has to be expected (LogPow > 3).
Results of PBT and vPvB assessment					No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>10- 100	mg/l	

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
Toxicity to fish:	LC50	96h	>1000	mg/l	Pimephales promelas		Analogous conclusion	
Toxicity to fish:	LC50	96h	10000	mg/l	Cyprinodon variegatus	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion	
Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		Analogous conclusion	
Toxicity to algae:	EC50	96h	>1000	mg/l	Selenastrum capricornutum		Analogous conclusion	
Persistence and degradability:		28d	16	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)		
Bioaccumulative potential:	Log Pow		>6,7			,		

Carbon dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other adverse effects:							Greenhouse effect

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Return to manufacturer with residual pressure.

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

SECTION 14: Transport information



Page 12 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

General statements

UN number: 1950

Transport by road/by rail (ADR/RID)

UN proper shipping name: UN 1950 AEROSOLS

Transport hazard class(es):

Packing group:

Classification code:

LQ (ADR 2015):

2.1

5F

LQ (ADR 2015):

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

AEROSOLS

Transport hazard class(es):

Packing group:

2.1

EmS: F-D, S-U Marine Pollutant: n.a

Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:

Aerosols, flammable

Transport hazard class(es): 2.1

Packing group:

Environmental hazards: Not applicable

Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Observe law on protection of expectant mothers (German regulation).

Directive 2010/75/EU (VOC): 493,4 g/l
Directive 2010/75/EU (VOC): ~ 56 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1 - 16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):









Page 13 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Sens. 1, H317	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on test data.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H372 Causes damage to organs through prolonged or repeated exposure by inhalation.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Skin Sens. — Skin sensitization

Aerosol - Aerosols

Asp. Tox. — Aspiration hazard

STOT RE — Specific target organ toxicity - repeated exposure

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight



Page 14 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Ca

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform ChemicaL Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential

ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.



Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0011

Replacing version dated / version: 30.07.2015 / 0010

Valid from: 21.08.2015 PDF print date: 26.08.2015 MULTI-SPRAY PLUS 7 500 mL

Art.: 3305

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) **UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF

VOC Volatile organic compounds

very persistent and very bioaccumulative vPvB

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) WEL-TWA, WEL-STEL reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.