

Page 1 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 27.01.2014 / 0010
Valid from: 21.08.2015
PDF print date: 02.09.2015
Keramik-Paste 400 mL
Art.: 3419

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Keramik-Paste 400 mL

Art.: 3419

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lubricant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Use in closed process, no likelihood of exposure.

PROC 2 - Use in closed, continuous process with occasional controlled exposure

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC11 - Non industrial spraying

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 8a - Wide dispersive indoor use of processing aids in open systems

ERC 8d - Wide dispersive outdoor use of processing aids in open systems

ERC 9a - Wide dispersive indoor use of substances in closed systems

ERC 9b - Wide dispersive outdoor use of substances in closed systems

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany

Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 27.01.2014 / 0010
Valid from: 21.08.2015
PDF print date: 02.09.2015
Keramik-Paste 400 mL
Art.: 3419

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H315-Causes skin irritation. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P280-Wear protective gloves.
P332+P313-If skin irritation occurs: Get medical advice/attention.
P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501-Dispose of contents/container to special waste collection point.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Possible build up of explosive/highly flammable vapour/air mixture.

Danger of bursting (explosion) when heated

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	---

Page 3 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 27.01.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 02.09.2015
 Keramik-Paste 400 mL
 Art.: 3419

content %	15-<20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	--
Index	649-467-00-8
EINECS, ELINCS, NLP	265-157-1
CAS	64742-54-7
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 If the person is unconscious, place in a stable side position and consult a doctor.
 Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.
 Keep Data Sheet available.

Ingestion

Call doctor immediately - have Data Sheet available.
 Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Nausea

Effects/damages the central nervous system

Narcotic effect.

With long-term contact:

Dermatitis (skin inflammation)

Drying of the skin.

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Page 4 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 27.01.2014 / 0010
Valid from: 21.08.2015
PDF print date: 02.09.2015
Keramik-Paste 400 mL
Art.: 3419

CO2
Extinction powder

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air mixture

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Only from a specialist.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Do not use the product in enclosed spaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

GB

Page 5 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 27.01.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 02.09.2015
 Keramik-Paste 400 mL
 Art.: 3419

Store product closed and only in original packing.
 Do not store with oxidizing agents.
 Observe special regulations for aerosols!
 Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

Chemical Name	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	Content %:15-<20
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: ---	
Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954)	
BMGV: ---	Other information: ---	
Chemical Name	Butane	Content %:
WEL-TWA: 600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	
BMGV: ---	Other information: ---	
Chemical Name	Isobutane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
BMGV: ---	Other information: ---	
Chemical Name	Silica, amorphous	Content %:
WEL-TWA: 6 mg/m ³ (total inh. dust), 2,4 mg/m ³ (resp. dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	149	mg/kg bw/day	

Page 6 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 27.01.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 02.09.2015
 Keramik-Paste 400 mL
 Art.: 3419

Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m ³	
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Protective nitrile gloves (EN 374)
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 > 480
 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).
 Boots (EN ISO 20347)
 PVC

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 At high concentrations:
 Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Page 7 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 27.01.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 02.09.2015
 Keramik-Paste 400 mL
 Art.: 3419

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol, Substance: Liquid
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	-60 °C
Evaporation rate:	n.a.
Flammability (solid, gas):	Not determined
Lower explosive limit:	1,4 Vol-%
Upper explosive limit:	32 Vol-%
Vapour pressure:	4200 hPa
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,728 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	510 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	58 %

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

Page 8 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 27.01.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 02.09.2015
 Keramik-Paste 400 mL
 Art.: 3419

See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Keramik-Paste 400 mL

Art.: 3419

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>=2000	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant, Analogous conclusion
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:						Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness.
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Aspiration hazard:						Yes

Page 9 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 27.01.2014 / 0010
Valid from: 21.08.2015
PDF print date: 02.09.2015
Keramik-Paste 400 mL
Art.: 3419

Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Symptoms:						headaches, fatigue, dizziness, nausea, cramps, itching
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Not irritant (respiratory tract).

Distillates (petroleum), hydrotreated heavy paraffinic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Skin corrosion/irritation:						Mild irritant, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitising
Aspiration hazard:						Yes
Aspiration hazard:						Yes, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						coughing, respiratory distress, nausea and vomiting., diarrhoea

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

Page 10 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 27.01.2014 / 0010
Valid from: 21.08.2015
PDF print date: 02.09.2015
Keramik-Paste 400 mL
Art.: 3419

Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Keramik-Paste 400 mL Art.: 3419							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							Product is slightly volatile.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	1 -10	mg/l			
Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to fish:	NOEC/NO EL		>1-<10	mg/l			
Toxicity to daphnia:	EC50		1 -<10	mg/l			
Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to daphnia:	NOEC/NO EL		<0,1-<1	mg/l			

Page 11 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 27.01.2014 / 0010
Valid from: 21.08.2015
PDF print date: 02.09.2015
Keramik-Paste 400 mL
Art.: 3419

Toxicity to daphnia:	NOEC/NO EL	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	IC50		10- <100	mg/l			
Persistence and degradability:							Readily biodegradable
Bioaccumulative potential:	BCF		242- 253				
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	DOC						DOC-elimination degree(complexing organic substance)>= 80%/28d:

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	NOEC/NO EL	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	LL50	96h	>10000	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to algae:	NOEC/NO EL	72h	>=100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:							Not readily biodegradable
Water solubility:							Insoluble

Propane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Butane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be

Page 12 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 27.01.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 02.09.2015
 Keramik-Paste 400 mL
 Art.: 3419

allocated under certain circumstances. (2014/955/EU)
 16 05 04 gases in pressure containers (including halons) containing hazardous substances
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 E.g. suitable incineration plant.
 E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.
 Recommendation:
 Do not perforate, cut up or weld uncleaned container.
 15 01 04 metallic packaging
 15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

UN number: 1950

Transport by road/by rail (ADR/RID)

UN proper shipping name:
 UN 1950 AEROSOLS
 Transport hazard class(es): 2.1
 Packing group: -
 Classification code: 5F
 LQ (ADR 2015): 1 L
 Environmental hazards: Not applicable
 Tunnel restriction code: D



Transport by sea (IMDG-code)

UN proper shipping name:
 AEROSOLS
 Transport hazard class(es): 2.1
 Packing group: -
 EmS: F-D, S-U
 Marine Pollutant: n.a.
 Environmental hazards: Not applicable



Transport by air (IATA)

UN proper shipping name:
 Aerosols, flammable
 Transport hazard class(es): 2.1
 Packing group: -
 Environmental hazards: Not applicable



Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.
 Observe restrictions:
 Comply with trade association/occupational health regulations.
 Observe youth employment law (German regulation).
 Directive 2010/75/EU (VOC):

58 %

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 27.01.2014 / 0010
Valid from: 21.08.2015
PDF print date: 02.09.2015
Keramik-Paste 400 mL
Art.: 3419

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1 - 16
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.
Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation
Asp. Tox. — Aspiration hazard
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Aerosol — Aerosols
Flam. Liq. — Flammable liquid
STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight

CAS	Chemical Abstracts Service
CEC	Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO	Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC	Collaborative International Pesticides Analytical Council
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
COD	Chemical oxygen demand
CTFA	Cosmetic, Toiletry, and Fragrance Association
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
DT50	Dwell Time - 50% reduction of start concentration
DVS	Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EC	European Community
ECHA	European Chemicals Agency
EEA	European Economic Area
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ERC	Environmental Release Categories
ES	Exposure scenario
etc.	et cetera
EU	European Union
EWC	European Waste Catalogue
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
HET-CAM	Hen's Egg Test - Chorionallantoic Membrane
HGWP	Halocarbon Global Warming Potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
IBC (Code)	International Bulk Chemical (Code)
IC	Inhibitory concentration
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
LC	lethal concentration
LC50	lethal concentration 50 percent kill
LCLo	lowest published lethal concentration
LD	Lethal Dose of a chemical
LD50	Lethal Dose, 50% kill
LDLo	Lethal Dose Low
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute of Occupational Safety and Health (United States of America)
NOAEC	No Observed Adverse Effective Concentration
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
ODP	Ozone Depletion Potential

Page 15 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 27.01.2014 / 0010
Valid from: 21.08.2015
PDF print date: 02.09.2015
Keramik-Paste 400 mL
Art.: 3419

OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.