

Small voltage cable

Li2GYw (SiHYw PV/P)



Application: As connecting cable between transformer and halogen lamps in low voltage lightning systems.

Construction and technical data:

Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	silicone rubber
Sheathing material:	PVC
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
Max. temperature at conductor, °C:	180 °C
Permitted outer cable temperature, fixed, °C:	-40 - +90 °C
Permitted outer cable temperature, moved, °C:	5 - 90 °C
Bending radius, fixed installation:	7.5 x Ø



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

Li2GYw (SiHYw PV/P)

Nominal voltage U:	24 V
Core identification:	red, blue

part no.	part name	RI [Ohm/km]	Rbv [mm]	w [mm]	h [mm]	Cu	G [kg]
031847	02X1.5	13.3	27	5.8	3.5	28,8	44
031848	02X2.5	7.98	30	6.8	4	48	66
031849	02X4	4.95	31	7.8	4.4	76,8	96

RI	Conductor resistance
Rbv	Bending radius, fixed installation
w	Width of (flat) cable approx.
h	Approx. height of (flat) cable
Cu	Copper weight (GER)
G	net weight per 1000