

NOTES: UNLESS OTHERWISE SPECIFIED

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER


2. MODIFICATIONS: N/A

## 3. SPECIFICATIONS:

- 3.1 CURRENT RATING: 7.5 AMPS
- 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
- 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
- 3.5 MOISTURE RESISTANCE: IP67 ( MATED CONDITION )
- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: ATM06-6S\* PLUG (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND REAR SEAL WIRE RANGE:							
	CONTACT	MIN. INSUL	MAX. INSUL	TYPICA			
	SIZE	0.0		WIRERAN			

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	
SIZE	O.D.	O.D.	WIRE RANGE	
20	1.35 mm (.053 in)	3.05 mm (.120 in)		



PART NUMBER CHART			
COLOR	PART NUMBER		
GREY	ATM04-6P		
BLACK	ATM04-6P-BLK		
BLUE	ATM04-6P-BLU		
BROWN	ATM04-6P-BRN		
GREEN	ATM04-6P-GRN		
RED	ATM04-6P-RED		
WHITE	ATM04-6P-WHT		
YELLOW	ATM04-6P-YEL		

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

	OFF DADTAI	LILADED OLIADE						
	SEEPARIN	OMBER CHART						
	PART N	NUMBER			DE	SCRIPTION		ITEM
QUANTITY		MA	TER	IAL	S LI	ST		
	WISE SPECIFIED	SIGNATUR	ATURES DATE A MODE A COL					
Tolerances are a     PL DEC +0.30	MATERIALS LIST  MISE SPECIFIED re in metric(mm). To stroke to the stroke	Amphenoi						
2 PL DEC ±0.15 3 PL DEC ±0.08		CHECKED:			Sir	e Systems - www.amphe	nol-sine.com	
3) Note reference	= /x	ENGINEER:						ITEM  REVISION  A3 1
MATERIAL SPECIFICA	7000	APPROVAL:				Clinton Township, MI 48036		
WATERIAL SPECIFICA	HONO.	CUSTOMER:			RECI	EPTACLE, 6 PIN. A	ATM SERIES	SERIES
PROCESS SPECIFICATIONS:  IN SI SI TH		INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION, NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL						
					C-			A3
NEXT ASS'Y:		MANUFACTURING VARIATIONS.		SCALE:	NONE		SHEET 1 OF	1