

MD 1060 & MD 1160 Voltage and Continuity Tester



MD 1060-LED
MD 1160-LCD

NEW
Voltage & Continuity Tester



A two-pole voltage detector is a basic tool kit for electricians. High quality rubber construction make this the professional's choice. Both models support Voltage measurement, Continuity measurement, Single pole test, Phase rotating field test and a torch function via a white LED for working in dark areas. The products are built in accordance to the latest voltage tester standard EN 61243-3:2010 and are GS approved by TÜV test lab.

Measuring functions:

- AC, DC voltage testing;
- Phase testing;
- Rotary field testing;
- Continuity testing.

Key Features:

- Voltage testing up to 690 V;
- Automatic AC/DC recognition;
- Continuity buzzer and led to indicate resistances below 500 k Ω ;
- Phase & Rotating Field Test;
- Auto Power Off;
- LED display (MD 1060), LCD display (MD 1160);
- Optical and Acoustic indication of Protective Extra Low Voltage.

APPLICATION:

- Mid level electrical testing;
- Mid level electronic fault finding;
- Field servicing;
- General purpose.

SPECIAL FEATURES

- IP64-protection degree
- CAT IV 600 V
- Automatic AC/DC recognition

STANDARDS

- Conforms to GS38,
- DIN VDE 0411 and IEC/EN 61243-3:2010



Technical Specification

	MD1060-LED	MD1160-LCD
AC Voltage		
Test Range	12 V ÷ 690 V	0 V ÷ 690 V
Response Time	<1s	<1s
Frequency Range	16 ÷ 400 Hz	16 ÷ 400 Hz
DC Voltage		
Test Range	12 V ÷ 690 V	0 V ÷ 690 V
Response Time	<1s	<1s
Continuity		
Indication	Acoustical and LED indication	Acoustical and LED indication
Continuity test (Acoustic)	0 ÷ 500 kΩ +50%	0 ÷ 500 kΩ +50%
Test Current	3.5 μA	3.5 μA
Phase Testing		
Phase Testing	Single-Pole Phase testing	Single-Pole Phase testing
Phase Sequence	Two-Pole Phase Sequence testing	Two-Pole Phase Sequence testing
Phase indication	>100 V AC	>100 V AC
Display		
Tolerance	12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V	0 V ÷ 690 V ± (3% ± 5dgt)
Safety & Protection		
Overload Category	CAT IV 600 V	CAT IV 600 V
Compliant to standards	IEC/EN 61243-3:2010, DIN VDE 0411, GS38	IEC/EN 61243-3:2010, DIN VDE 00411, IEC 61010-1, GS38
Protection degree	IP64 For outdoor use: Water jet and dust tight protection	IP64 For outdoor use: Water jet and dust tight protection
Temperature range	-15 ÷ 55 °C	-15 ÷ 55 °C
Power supply	2 x 1,5 V Type AAA Micro	2 x 1,5 V Type AAA Micro
Dimensions		
Weight	200 g	200 g
Dimensions	240 x 60 x 20 mm	240 x 60 x 20 mm

Ordering information

Standard set

MD 1060-LED




- Instrument MD 1060-LED
- Plastic probe guard in accordance with GS 38, 2 pcs
- 1.5 V battery, type AAA, 2 pcs
- Instruction manual

Ordering information

Standard set

MD 1160-LCD



- Instrument MD 1160-LCD
- Plastic probe guard in accordance with GS 38, 2 pcs
- 1.5 V battery, type AAA, 2 pcs
- Instruction manual

Recommended accessories

- Calibration certificate



Measuring and Regulation Equipment Manufacturer

METREL d.d.
Ljubljanska 77
SI-1354 Horjul
Tel: + 386 (0)1 75 58 200
Fax: + 386 (0)1 75 49 226
E-mail: metrel@metrel.si
http://www.metrel.si

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery. Subject to technical change without notice.