



KA-10/1PACK

Order No.: 25.3120

PRODUCTINFOS

Wireless 16-channel PLL audio transmission system for cameras

- Consisting of a portable audio transmitter and receiver
- Frequency range: 863-865 MHz
- Transmitter and receiver with rechargeable lithium-ion batteries for reducing the weight and to ensure long operating times
- Transmitter can also be used for transmitting line signals (adjustment via recessed gain control)
- Receiver with 3-step PAD switch (0dB/-10 dB/-20 dB) for perfect level matching to the audio input of the camera
- Transmitter and receiver are fitted with a robust metal fixing clip
- Operating time: approx. 12 hours
- Supplied with lavalier microphone in skin design with windshield and tie clip, attachment clip for camera mounting, trim key, dual charging slot with plug-in switch-mode PSU, connection cable with 3.5 mm plug to 3.5 mm plug, connection cable with 3.5 mm plug to XLR plug

**Licence-free in the EU.
Supplied w/o camera.**

TECHNICAL SPECIFICATIONS

KA-10/1PACK

Type	16-channel PLL audio transmission system
Carrier frequency range	863-865 MHz
Audio frequency range	40-18,000 Hz
Channels	16
THD	< 1 %
Admiss. ambient temp.	0-40 °C
Transmitting power	< 10 mW
Operating range	approx. 60 m
Power supply transmitter	3.7 V rech. lithium-ion battery
Width transmitter	55 mm
Height transmitter	100 mm
Depth transmitter	18 mm
Weight transmitter	80 g
Audio signal receiver	300 mV/7 kΩ (jack)
Power supply receiver	3.7 V rech. lithium-ion battery
Width receiver	55 mm
Height receiver	100 mm
Depth receiver	18 mm
Weight receiver	82 g
Connections receiver	1 x 3.5 mm jack (transmitter) 1 x 3.5 mm jack (receiver)

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.