

according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Varybond Regular Grade

Further trade names

.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants, greases, release products

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Am Eichenbach 14
Place: D-73054 Eislingen/Fils
Telephone: +49 800 6273002
e-mail: info@itwcp.de
Internet: itwcp.de

Responsible Department: Produktsicherheit Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

Swiss Toxicological Information Centre - Téléphone : +41 44 251 51 51 (in

Switzerland dial 145)

United Kingdom: National Poisons Information Service - Phone number:

8448920111

Österreich: Vergiftungsinformationszentrale Vienna - Telefon-Nummer: +43 1

406 43 43

Schweiz: Tox Info Suisse - Telefon-Nummer: +41 44 251 51 51 España: Instituto Nacional de Toxicología - Teléfono: +34 91 562 04 20 România (Romania): Spitalul de Urgenta Floreasca 021 230 8000

1.4. Emergency telephone

number:

Deutschland: ++49 800 6273002

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Toxic to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Pictograms:



Hazard statements

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P391 Collect spillage.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.



according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 2 of 10

P273 Avoid release to the environment.

2.3. Other hazards

Ergebnisse der PBT- und vPvB-Beurteilung

PBT: Nicht anwendbar. PvB: Nicht anwendbar.

Results of PBT and vPvB assessment

PBT

Not applicable.

PvB

Not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation))	•		
1314-13-2	zinc oxide			2,5-10 %	
	215-222-5	030-013-00-7	01-2119463881-22		
	Aquatic Acute 1, Aquatic Chronic 1	; H400 H410			
	Copper pigments				
	231-159-6		01-2119480154-42		
	Flam. Sol. 2, Acute Tox. 3, Acute T H331 H302 H319 H400 H410	quatic Chronic 1; H228			
7429-90-5	aluminium powder (stabilised)		2,5-10 %		
	231-072-3	013-002-00-1	01-2119529243-45		
	Flam. Sol. 1, Water-react. 2; H228	•			
68457-79-4	Phosphorodithioic acid, mixed O,O	alts	<1%		
	270-608-0				
	Skin Irrit. 2, Eye Dam. 1, Aquatic C				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

	=	*****	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
1314-13-2	215-222-5	zinc oxide	2,5-10 %
	dermal: LD50	= >5000 mg/kg; oral: LD50 = > 5000 mg/kg	
	231-159-6	Copper pigments	2,5-7 %
	1	E = 3 mg/l (vapours); inhalation: LC50 = 0,7 mg/l (dusts or mists); dermal: LD50 = oral: LD50 = 400 mg/kg	
7429-90-5	231-072-3	aluminium powder (stabilised)	2,5-10 %
	oral: LD50 = 1	5900 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary. In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Provide fresh air.

ITW LLC & Co. KG



Safety Data Sheet

according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 3 of 10

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If swallowed, immediately drink: Water. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Extinguishing powder. Carbon dioxide (CO2). Foam.

Unsuitable extinguishing media

Water. Water with tenside additive.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains. In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Wear personal protection equipment. Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

No data available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Special danger of slipping by leaking/spilling product. Avoid contact with eyes and skin.



according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 4 of 10

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. .

Further information on handling

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe in addition any national regulations!

Hints on joint storage

Observe in addition any national regulations!

Further information on storage conditions

Storage temperature: 10-30°C Storage humidity range: 30-50%

7.3. Specific end use(s)

Lubricant, lubrifiants and release products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7429-90-5	Aluminium metal, respirable dust	-	4		TWA (8 h)	WEL

Additional advice on limit values

No data available

8.2. Exposure controls





Appropriate engineering controls

Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. EN 166

Hand protection

EN ISO 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Personal protection equipment

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Environmental exposure controls

Clean contaminated articles and floor according to the environmental legislation.

ITW LLC & Co. KG



Safety Data Sheet

according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 5 of 10

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste
Colour: dark grey
Odour: characteristic
Odour threshold: No data available

Test method

Flammability: ISO 10156

Flash point: 210 °C

Solubility in other solvents

No data available

Density: 1,21 g/cm³

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Oxidizing properties

No data available

Further Information

Keine weiteren relevanten Informationen verfügbar.

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Protect from moisture.

10.5. Incompatible materials

Do not mix with acids. Do not mix with alkali.

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 6 of 10

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
1314-13-2	zinc oxide						
	oral	LD50 mg/kg	> 5000	Rat	ECHA		
	dermal	LD50 mg/kg	>5000	Rat	ECHA		
	Copper pigments						
	oral	LD50 mg/kg	400	Ratte	ECHA		
	dermal	LD50 mg/kg	>2000	Ratte	ECHA		
	inhalation vapour	ATE	3 mg/l				
	inhalation (4 h) dust/mist	LC50	0,7 mg/l	Ratte	ECHA		
7429-90-5	aluminium powder (stabilised)						
	oral	LD50 mg/kg	15900	Ratte	ECHA		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

No data available

Sensitising effects

Based on available data, the classification criteria are not met. not sensitising.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met. No data available

STOT-single exposure

Based on available data, the classification criteria are not met. No data available

STOT-repeated exposure

Based on available data, the classification criteria are not met. No data available

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information

No data available

SECTION 12: Ecological information

12.1. Toxicity



according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 7 of 10

Ökologie Wasser: Giftig für Wasserorganismen, mit langfristiger Wirkung

Gewässergefährdend, kurzfristige (akut): Nicht eingestuft

Gewässergefährdend, langfristige (chronisch): Giftig für Wasserorganismen, mit langfristiger Wirkung

Ecology Water: Toxic to aquatic life with long lasting effects

Hazardous to the aquatic environment, short-term (acute): Not classified

Hazardous to the aquatic environment, long-term (chronic): Toxic to aquatic life with long lasting effects

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
1314-13-2	zinc oxide						
	Acute fish toxicity	LC50 mg/l	0,112	96 h	Fisch	ECHA	
	Acute algae toxicity	ErC50	0,3 mg/l	96 h	Alge	ECHA	
	Acute crustacea toxicity	EC50 mg/l	0,360		wirbellose Wasserlebewesen	ECHA	

12.2. Persistence and degradability

Keine zusätzlichen Informationen vorhanden, No additional information available

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40 °C). It contains relatively few normal paraffins.] (64742-52-5)

12.4. Mobility in soil

Keine zusätzlichen Informationen vorhanden, No additional information available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

Keine zusätzlichen Informationen vorhanden, No additional information available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Keine zusätzlichen Informationen vorhanden, No additional information available

12.7. Other adverse effects

Keine zusätzlichen Informationen vorhanden, No additional information available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

120112 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF

METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; spent waxes and fats; hazardous waste

List of Wastes Code - contaminated packaging



according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 8 of 10

200139 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately

collected fractions (except 15 01); Plastics

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Zinkoxid)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Classification code: M7

Special Provisions: 274 335 601

Limited quantity:5 kgTransport category:3Hazard No:90Tunnel restriction code:E

Other applicable information (land transport)

E,

Inland waterways transport (ADN)

14.1. UN number or ID number: UN3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc

oxide)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Classification code: M7
Special Provisions: 274 601
Limited quantity: 5 kg

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

14.1. UN number or ID number: UN3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc

oxide) 9

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9





according to UK REACH Regulation

Varybond Regular Grade

Revision date: 14.02.2023 Product code: RG Page 9 of 10

Marine pollutant:YesSpecial Provisions:274, 335Limited quantity:5 kgEmS:F-A, S-F

Other applicable information (marine transport)

E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(Zinc

oxide)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: A97 A158 A179

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger:956IATA-max. quantity - Passenger:400 kgIATA-packing instructions - Cargo:956IATA-max. quantity - Cargo:400 kg

Other applicable information (air transport)

E1 : Y956

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

Keine weiteren relevanten Informationen verfügbar.

No further relevant information available.

14.7. Maritime transport in bulk according to IMO instruments

Keine weiteren relevanten Informationen verfügbar.

No further relevant information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H228 Flammable solid.



according to UK REACH Regulation

	Varybond Regular Grade					
Revision date: 14.02.2023	Product code: RG	Page 10 of 10				
H261	In contact with water releases flammable gases.					
H302	Harmful if swallowed.					
H315	Causes skin irritation.					
H318	Causes serious eye damage.					
H319	Causes serious eye irritation.					
H331	Toxic if inhaled.					
H400	Very toxic to aquatic life.					
H410	Very toxic to aquatic life with long lasting effects.					
H411	Toxic to aquatic life with long lasting effects.					

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)