

Page 1 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Pro-Line Electronic-Spray 400 ml

Art.: 7386

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC11 - Non industrial spraying

PROC13 - Treatment of articles by dipping and pouring

PROC17 - Lubrication at high energy conditions and in partly open process

PROC18 - Greasing at high energy conditions

PROC19 - Hand-mixing with intimate contact and only PPE available

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 2 - Formulation of preparations

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 5 - Industrial use resulting in inclusion into or onto a matrix

ERC 8a - Wide dispersive indoor use of processing aids in open systems

ERC 8c - Wide dispersive indoor use resulting in inclusion into or onto a matrix

ERC 8d - Wide dispersive outdoor use of processing aids in open systems

ERC 8f - Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany

Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification



Page 2 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard statement Hazard category

Asp. Tox. H304-May be fatal if swallowed and enters airways. 1

Aerosol 1 H222-Extremely flammable aerosol.

1 H229-Pressurised container: May burst if heated. Aerosol

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

EUH208-Contains Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a. **3.2 Mixture**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	(64742-48-9)
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

	3-alkyl derivs., distn. residues, sulfonated, calcium salts
--	---



Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	307-593-8
CAS	97675-24-6
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Effects/damages the central nervous system

With long-term contact:

Dermatitis (skin inflammation)

Product removes fat.

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2

Foam

Extinction powder

Water jet spray

Unsuitable extinguishing media

High volume water jet



Page 4 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Hydrocarbons

Toxic pyrolysis products.

Danger of bursting (explosion) when heated

Explosive vapour/air mixture

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Do not store with oxidizing agents.

Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").

Keep protected from direct sunlight and temperatures over 50°C.



(GR)

Page 5 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

Store in a well ventilated place. 7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Content %:25-50
WEL-TWA: 800 mg/m3	WEL-STEL:	
Monitoring procedures:	 Draeger - Hydrocarbons 2/a (81 03 581) 	
	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 	
	- Compur - KITA-187 S (551 174)	
BMGV:	Other information:	(WEL acc. to RCP-method,
	EH40)	

Chemical Name	Oil mist, mineral	Content %	ó:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)		
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371)		
	- Draeger - Oil Mist 1/a (67 33 031)		
BMGV:	Other information:		

Chemical Name	Hydrocarbons, C3-4	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: 1250 ppm (2180 mg/m3) (Liquefied petroleum gas (LPG))	
Monitoring procedures:		
BMGV:	Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,3

Permeation time (penetration time) in minutes:

> 120

Protective hand cream recommended.



(GR)

Page 6 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol, Substance: Liquid

Colour: Not determined Odour: Characteristic Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined

Flash point: n.a. Not determined Evaporation rate: Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: 0,71 g/ml Bulk density: n.a.

Not determined Solubility(ies): Water solubility: Insoluble Not determined Partition coefficient (n-octanol/water):

Auto-ignition temperature: Not determined Decomposition temperature: Not determined

Viscosity:

Explosive properties: Product is not explosive. Possible build up of explosive/highly

flammable vapour/air mixture.

Oxidising properties:

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Not determined Conductivity: Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity



Page 7 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effectsPossibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t					
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
cute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
espiratory or skin sensitisation:						n.d.a.
erm cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
eproductive toxicity:						n.d.a.
pecific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
peated exposure (STOT-RE):						
piration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alka						
Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t					
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8	Rat	OECD 403 (Acute	
			h		Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may
						cause skin dryness or
						cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin sensitisation:					OECD 406 (Skin	Not sensitizising
					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative, Analogous
					Reverse Mutation Test)	conclusion



Page 8 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

Carcinogenicity:	OECD 453 (Combined Negative, Analogous
	Chronic conclusion
	Toxicity/Carcinogenicity
	Studies)
Reproductive toxicity:	OECD 414 (Prenatal Negative, Analogous
	Developmental conclusion
	Toxicity Study)
Reproductive toxicity:	OECD 421 Negative, Analogous
	(Reproduction/Develop conclusion
	mental Toxicity
	Screening Test)
Specific target organ toxicity -	No indications of such an
single exposure (STOT-SE):	effect.
Specific target organ toxicity -	OECD 408 (Repeated No indications of such an
repeated exposure (STOT-RE):	Dose 90-Day Oral effect., Analogous
	Toxicity Study in conclusion
	Rodents)
Aspiration hazard:	Yes
Symptoms:	unconsciousness,
	headaches, dizziness

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts									
Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes			
	t								
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat					
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat					
Skin corrosion/irritation:				Rabbit		Not irritant			
Serious eye damage/irritation:				Rabbit		Not irritant			
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative			
					Reverse Mutation Test)	_			

Hydrocarbons, C3-4							
Toxicity / effect	Endpoin t	Value	Unit	Organism	Test method	Notes	
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	10000	ppm	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)		

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Pro-Line Electronic-Spray 400 ml Art.: 7386 Toxicity / effect Endpoint Time Value Unit Organism Test method Notes Toxicity to fish: n.d.a. Toxicity to daphnia: n.d.a. Toxicity to algae: n.d.a. Persistence and n.d.a. degradability: Bioaccumulative n.d.a. potential: Mobility in soil: n.d.a. Results of PBT and n.d.a. vPvB assessment Other adverse effects: n.d.a. Other information: According to the recipe, contains no AOX.



Page 9 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
				_	mykiss	Acute Toxicity	
						Test)	
Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell	OECD 201	
					a subcapitata	(Alga, Growth	
						Inhibition Test)	
Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriell	OECD 201	
					a subcapitata	(Alga, Growth	
						Inhibition Test)	
Persistence and		28d	80	%		OECD 301 F	
degradability:						(Ready	
						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
Bioaccumulative	Log Pow		5,5-7,2				
potential:	1 1/						
Mobility in soil:	Log Koc		>3				N DDT I / N
Results of PBT and							No PBT substance, No
vPvB assessment			1.0	4			vPvB substance
Water solubility:			~10	mg/l			Slight
Water solubility:							Insoluble

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	>1000	mg/l	Pimephales promelas		Analogous conclusion
Toxicity to fish:	LC50	96h	10000	mg/l	Cyprinodon variegatus	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	,	Analogous conclusion
Toxicity to algae:	EC50	96h	>1000	mg/l	Selenastrum capricornutum		Analogous conclusion
Persistence and degradability:		28d	16	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
Bioaccumulative potential:	Log Pow		>6,7			,	

Hydrocarbons, C3-4							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to daphnia:	LC50	48h	14,22	mg/l	Daphnia magna		calculated value
Bioaccumulative	Log Pow		1,1-2,8				
potential:							

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)



(GB)

Page 10 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

07 06 99 wastes not otherwise specified

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations. Take full aerosol cans to problem waste collection. Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

UN number: 1950

Transport by road/by rail (ADR/RID)

UN proper shipping name:
UN 1950 AEROSOLS
Transport hazard class(es):
Packing group:
Classification code:
LQ (ADR 2015):

2.1
5F
LD (ADR 2015):
1 L

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

AEROSOLS

Transport hazard class(es):

Packing group:

EmS:

2.1

F-D.

EmS: F-D, S-U Marine Pollutant: n.a

Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:

Aerosols, flammable

Transport hazard class(es): 2.1

Packing group: -

Environmental hazards: Not applicable

Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Observe incident regulations.

Directive 2010/75/EU (VOC):

~ 70.5% %









Page 11 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1 - 16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

Asp. Tox. — Aspiration hazard

Aerosol — Aerosols

Skin Sens. — Skin sensitization

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (RÉGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association



(GB)

Page 12 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level DOC Dissolved organic carbon

Dwell Time - 50% reduction of start concentration DT50

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

ΕČ **European Community** ECHA European Chemicals Agency EEA European Economic Area European Economic Community EEC

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

FΝ European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera ΕU **European Union**

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential International Agency for Research on Cancer IARC International Air Transport Association IATA

Intermediate Bulk Container IBC

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl.

IUCLID International Uniform Chemical Information Database

I C lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level

LQ **Limited Quantities**

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

No Observed Adverse Effective Concentration NOAFC

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon persistent, bioaccumulative and toxic PBT

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

parts per million ppm



(GB)

Page 13 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.08.2015 / 0011

Replacing version dated / version: 08.11.2013 / 0010

Valid from: 07.08.2015 PDF print date: 10.08.2015 Pro-Line Electronic-Spray 400 ml

Art.: 7386

PROC Process category Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Telephone Tel.

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average)

reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.