

DATASHEET

BOPP Packing Tape Item no.

Version 8/15

Performance Index

BOPP Tape Item: Test Mode Item Units Performance N/25mm GB/T 2792-1998 180°Peel Strength N/25mm GB/T 4850-2002 ≤2.8 180°To Backing mm/h·23 °C ·25mm×25mi ≤0.3 GB/T 4851-1998 Holding Power GB/T 4852-2002 ≥13 Initial Tack BOPP Substrate g/m² Seclusion Paper 0.028±0.002 GB/T 7125-1999 mm Substrate Thickness 0.050±0.002 GB/T 7125-1999 mm Adhesion Thickness / Acrylic Adhesives Clear/Brown Color N/10mm ≥30 GB/T 7753-1987 Tensile Strength GB/T 7753-1987 ≤180 Breakpoint Elongation $^{\circ}$ C Heat Resistance GB/T 7123.2-2002 Year Storage Life Min GB/T 13353-1992 Solvent Resistance GB/T 15903-1995 Resistance Flammability excellent Weathers packing, bunding etc. Remark



This data sheet is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com). All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This data represent the technical status at the time of printing. Changes in technology and equipment reserved.

Distributed Conrad Electronic SE

[©] Copyright 2013 by Conrad Electronic SE.