

DIN-Rail Adapter for Keystone or Fiber Optic Modules



✓ Ideal for apartment distributor

✓ Entry of keystones

✓ Entry of LC couplers

✓ A system for all DIN-rails

Abstract

DIN-Rail adapter for 1x Keystone Modules, IP20, inclusive labeling field, dust cover, earthing spring, side cover

Product Overview

The Keystone Module is mounted in Housing on a DIN-Rail. The distance of the DIN-Rail to the back plate of the cabinet should be about 10 mm. Up to 12 Keystone Modules can be installed in a row in the distribution panel. IP20 protection is guaranteed, when the Keystone Housing is mounted with site covers. The delivery does not contain Keystone Modules.

Features

- Layout keystone entry: 45° vertical outlet
- Area of application: Electrical distribution box
- Norms: ISO/IEC 11801 2nd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
 - Suitable for installation on DIN-Rail in electrical distribution boxes
 - Integrated dust cover
 - Lateral cover caps included
 - Protection class IP20
- Technical properties:
 - Housing material: ABS UL-94V-0
- Physical properties:
 - Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

Product Number

AN-25187

Technische Zeichnungen

