

DESIGN KIT

WE-PD SMD Shielded Power Inductor

**SIZE:**

7345 / 1260

TECHNICAL DATA:

L: 1 ~ 68 μ H
DCR: 4 ~ 239 m Ω
 I_{R^*} : 0.87 ~ 10.5 A
 I_{sat}^* : 0.95 ~ 12.5 A

Order Code 744 777**Version 1.0**

WE-PD SMD Shielded Power Inductor



7345	744 777 900 1	744 777 900 15	744 777 900 2	7345	744 777 900 3	744 771 003	744 771 004	744 771 006
	L: 1 μ H	L: 1.5 μ H	L: 2.2 μ H		L: 3.3 μ H	L: 3.5 μ H	L: 4.7 μ H	L: 6.8 μ H
	DCR: 10 m Ω	DCR: 15 m Ω	DCR: 16 m Ω		DCR: 26 m Ω	DCR: 5 m Ω	DCR: 8 m Ω	DCR: 14 m Ω
	I_{R^*} : 5.3 A	I_{R^*} : 4.3 A	I_{R^*} : 4.2 A		I_{R^*} : 3.3 A	I_{R^*} : 9.25 A	I_{R^*} : 8.25 A	I_{R^*} : 6.25 A
	I_{sat} : 9.5 A	I_{sat} : 7.3 A	I_{sat} : 6 A		I_{sat} : 4.5 A	I_{sat} : 9 A	I_{sat} : 8 A	I_{sat} : 6.4 A
	744 777 900 4	744 777 900 6	744 777 900 8		744 777 910	744 771 008	744 771 10	744 771 112
	L: 4.7 μ H	L: 6.8 μ H	L: 8.2 μ H		L: 10 μ H	L: 8.2 μ H	L: 10 μ H	L: 12 μ H
	DCR: 28 m Ω	DCR: 33 m Ω	DCR: 47 m Ω		DCR: 45 m Ω	DCR: 14 m Ω	DCR: 18 m Ω	DCR: 23 m Ω
	I_{R^*} : 3.16 A	I_{R^*} : 2.91 A	I_{R^*} : 2.7 A		I_{R^*} : 2 A	I_{R^*} : 6.25 A	I_{R^*} : 5 A	I_{R^*} : 3.91 A
	I_{sat} : 4.4 A	I_{sat} : 3.3 A	I_{sat} : 3 A		I_{sat} : 2.6 A	I_{sat} : 6.25 A	I_{sat} : 5.5 A	I_{sat} : 4.85 A
	744 777 911 2	744 777 911 5	744 777 911 8		744 777 912 2	744 771 115	744 771 118	744 771 122
	L: 12 μ H	L: 15 μ H	L: 18 μ H		L: 22 μ H	L: 15 μ H	L: 18 μ H	L: 22 μ H
DCR: 50 m Ω	DCR: 70 m Ω	DCR: 80 m Ω	DCR: 90 m Ω	DCR: 25 m Ω	DCR: 29 m Ω	DCR: 31 m Ω		
I_{R^*} : 1.82 A	I_{R^*} : 1.6 A	I_{R^*} : 1.5 A	I_{R^*} : 1.41 A	I_{R^*} : 3.75 A	I_{R^*} : 3.48 A	I_{R^*} : 3.37 A		
I_{sat} : 2.4 A	I_{sat} : 2.2 A	I_{sat} : 2.05 A	I_{sat} : 1.7 A	I_{sat} : 4.55 A	I_{sat} : 4.3 A	I_{sat} : 3.77 A		
744 777 912 7	744 777 913 3	744 777 913 9	744 771 001	744 771 127	744 771 133	744 771 139		
L: 27 μ H	L: 33 μ H	L: 39 μ H	L: 1.5 μ H	L: 27 μ H	L: 33 μ H	L: 39 μ H		
DCR: 120 m Ω	DCR: 140 m Ω	DCR: 145 m Ω	DCR: 4 m Ω	DCR: 40 m Ω	DCR: 49 m Ω	DCR: 57 m Ω		
I_{R^*} : 1.24 A	I_{R^*} : 1.13 A	I_{R^*} : 1.11 A	I_{R^*} : 10.5 A	I_{R^*} : 2.97 A	I_{R^*} : 2.68 A	I_{R^*} : 2.49 A		
I_{sat} : 1.55 A	I_{sat} : 1.4 A	I_{sat} : 1.23 A	I_{sat} : 12.5 A	I_{sat} : 3.55 A	I_{sat} : 3 A	I_{sat} : 2.74 A		
744 777 914 7	744 777 915 6	744 777 916 8	744 771 002	744 771 147	744 771 156	744 771 168		
L: 47 μ H	L: 56 μ H	L: 68 μ H	L: 2.2 μ H	L: 47 μ H	L: 56 μ H	L: 68 μ H		
DCR: 190 m Ω	DCR: 228 m Ω	DCR: 239 m Ω	DCR: 5 m Ω	DCR: 72 m Ω	DCR: 87 m Ω	DCR: 96 m Ω		
I_{R^*} : 1.03 A	I_{R^*} : 0.93 A	I_{R^*} : 0.87 A	I_{R^*} : 10 A	I_{R^*} : 2.21 A	I_{R^*} : 2.01 A	I_{R^*} : 1.91 A		
I_{sat} : 1.1 A	I_{sat} : 1.05 A	I_{sat} : 0.95 A	I_{sat} : 11 A	I_{sat} : 2.6 A	I_{sat} : 2.35 A	I_{sat} : 2.19 A		
1260				1260				

EMC COMPONENTS | INDUCTORS | TRANSFORMERS | RF COMPONENTS | CIRCUIT PROTECTION | EMC SHIELDING MATERIAL | CONNECTORS | SWITCHES | ASSEMBLY TECHNIQUE | POWER ELEMENTS

Important information: Würth Elektronik's design kits contain reference components. These components correspond with the current product development status on the day of supply. Exchange of the reference components to components with up-to-date product development status is not carried out automatically. No liability is taken for the use of these reference components. Therefore, please request new samples prior to releases for series production and product release.

Please check datasheets on www.we-online.com for specifications. Würth Elektronik eiSos GmbH & Co. KG, EMC & Inductive Solutions. © 2012