

# MULTILUBE PRO

---

## Technical Data Sheet

---

Product name: Multilube Pro  
Sales code: 32697

Creation date: 8/2016

Version: I

---

### 1: General description

Multilube Pro is a transparent multipurpose lubricant for general use by automotive professionals. It exhibits strong adhesion to the substrate, is non-dripping, good penetrating, resistant to high pressure and has excellent water repellence. The temporary blue aspect ensures reliable visible checking of coverage for reduced wear.

### 2: Features

- Provides long lasting lubrication.
- Produces a very low coefficient of friction.
- Reduces stick and slip problems.
- Excellent water resistance.
- Functional over a wide temperature range.
- Adheres strongly and resists lubricating film creep
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.

### 3: Applications

- Lubricating mechanical parts
- Handling equipment
- Chains
- Bearings
- Railroad equipment
- Agricultural equipment
- Surface treatment
- Guide rails
- Hinges
- Cables

### 4: Directions

- Do not mix with other products
- Apply to a clean, dry, degreased surface
- Apply a thin even film
- Allow a few minutes for good penetration
- Do not use on energized equipment
- To remove residues or excess product, use Power Clean Pro
- A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products



## 5: Typical product data (without propellant)

- Appearance : viscous liquid
- Colour : blue/transparent
- Odour : solvent
- Density : 0.80 g/cm<sup>3</sup> (@ 20°C)
- Flash Point : < 0 °C
- Density active product : 0.87 (@ 25°C)
- Flash point active product : 230 °C (Open Cup)
- Dynamic viscosity active product : 1894 mPa.s (@ 40°C)
- 4-ball wear active product : 0.25 mm<sup>2</sup>
- Operating temperature active product : -35 -> 200 °C

## 6: Packaging

Aerosol

12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.