


	SHORT X2				
NON FLUSH					
M8 conn	M12 conn	cable			
3 mm	3 mm	3 mm			
IS-08-H1-S1	IS-08-H1-S2	IS-08-H1-03			
958066960	958066690	95B066480			
IS-08-H2-S1	IS-08-H2-S2	IS-08-H2-03			
95B066990	95B063301	95B066500			
IS-08-H3-S1	IS-08-H3-S2	IS-08-H3-03			
958066910	95B066640	95B066420			
IS-08-H4-S1	IS-08-H4-S2	IS-08-H4-03			
95B063251	95B063241	95B066460			
10-30 Vdc (-15/10%)	10-30 Vdc (-15/10%)	10-30 Vdc (-15/10%)			
< 10%	< 10%	< 10%			
< 10%	< 10%	< 10%			
200mA	200mA	200mA			
< 10 mA	< 10 mA	< 10 mA			
< 1,2 V (I=100mA)	< 1,2 V (I=100mA)	< 1,2 V (I=100mA)			
Yellow	Yellow	Yellow			
500 Hz	500 Hz	500 Hz			
< 75 ms	< 75 ms	< 75 ms			
< 3%	< 3%	< 3%			
Present (self-resetting)	Present (self-resetting)	Present (self-resetting)			
Against polarity reversal inductive loads	Against polarity reversal inductive loads	Against polarity reversal inductive loads			
(-25 +60 °C)	(-25 +60 °C)	(-25 +70 °C)			
IP67	IP67	IP67			
		2 m			
		3 x 0,14 mm²			
Nickel-plated brass	Nickel-plated brass	Nickel-plated brass			
		80 g			
35g	55g				





M12 3 pole



		CONFIGU			
Available	Contacts numbers				
AVEIBOID	1	2	3	4	
(NO or NC)	+		-	NO/NC	

M8 3 pole

	ACTS CON	FIGURAT	ION	
Contractory	Contacts numbers			
Available	1 HIGHN	3 10.0	4 BACK	
NPN/PNP	1		NONC	