


	SH	ORT		
FLU	FLUSH		NON FLUSH	
M12 conn	cable	M12 conn	cable	
5 mm	5 mm	8 mm	8 mm	
IS-18-B1-S2	IS-18-B1-03	IS-18-D1-S2	IS-18-D1-03	
95B062151	95B062141	95B062551	95B062541	
IS-18-B2-S2	IS-18-B2-03	IS-18-D2-S2	IS-18-D2-03	
95B062171	95B062161	95B062571	95B062561	
IS-18-B3-S2	IS-18-B3-03	IS-18-D3-S2	IS-18-D3-03	
95B062111	95B062101	95B062511	95B062501	
IS-18-B4-S2	IS-18-B4-03	IS-18-D4-S2	IS-18-D4-03	
95B062131	95B062121	95B062531	95B062521	
10-30 Vdc (-15/10%)	10-30 Vdc (-15/10%)	10-30 Vdc (-15/10%)	10-30 Vdc (-15/10%)	
< 10%	< 10%	< 10%	< 10%	
< 10%	< 10%	< 10%	< 10%	
200 mA	200 mA	200 mA	200 mA	
< 10 mA	< 10 mA	< 10 mA	< 10 mA	
< 1,8 V (I=100mA)				
Yellow	Yellow	Yellow	Yellow	
1000 Hz	1000 Hz	1000 Hz	1000 Hz	
< 50 ms	< 50 ms	< 50 ms	< 50 ms	
< 3%	< 3%	< 3%	< 3%	
Present (self-resetting)	Present (self-resetting)	Present (self-resetting)	Present (self-resetting)	
Against polarity reversal inductive loads				
(-25 +60 °C)	(-25 +60 °C)	(-25 +60 °C)	(-25 +60 °C)	
IP67	IP67	IP67	IP67	
	2 m		2 m	
	3 x 0,25 mm²		3 x 0,25 mm²	
Nickel-plated brass	Nickel-plated brass	Nickel-plated brass	Nickel-plated brass	
	145g		145g	


95g

95g


2 wires NO or NC



3 wires PNP or NPN



4 wires (PNP/NPN, NO/NC)



M12 connector - connections



2 wires NO or NC

Accessors.	Contacts numbers			
Available .	1	2	3	4
NO	+		-	
NC	22		+	

3 wires

C	ONTACT	S CONFIGU	RATION	
Acceptable	2.44	Contacts	200	
Avaracie	-1	2	3	4
(NO or NC)	+		-	NO/NC

4 wires (PNP/NPN, NO/NC)

	Contacts numbers			
Output	.1.	2	3	- 4
NPN NO	+	NO	-	-
NPN NC	-	NC	+	-
PNP NO	+	+:	-	NO
PNP NC		+	+	NO