

FEATURES

- SIZES K(0402), J (0603), D (0805), C (1008), E (1206), A (1210) and B (1812)
- HIGH Q, HIGH CURRENT AND HIGH SRF CHARACTERISTICS
- REFLOW SOLDERING APPLICABLE
- HIGH INDUCTANCE AVAILABLE IN SMALL SIZE
- EMBOSSED PLASTIC CARRIER PACKAGING FOR AUTOMATIC PICK-PLACE*

*0402 PUNCHED CARDBOARD CARRIER

Specifications	Case Size Code			
	0402 (K)	0603 (J)	0805 (D)	1008 (C)
Inductance Range	1.8nH ~ 120nH	1.6nH ~ 470nH	2.2nH ~ 1.0µH	4.7nH ~ 8.2µH
Inductance Tolerance	See Product Standard Values Tables			
Operating Temperature Range	-40°C ~ +125°C			

Specifications	1206 (E)	1210 (A)	1812 (B)
	Inductance Range	3.3nH ~ 1.2µH	3.9nH ~ 8.6µH
Inductance Tolerance	See Product Standard Values Tables		
Operating Temperature Range	-40°C ~ +125°C		

ENVIRONMENTAL CHARACTERISTICS





Test	Specifications	Test Method & Condition
Solderability	75% Min. Coverage	After 3 sec. dip in +230°C soldering pot (post flux)
Resistance to Soldering Heat	(1) No evidence of damage (2) Inductance change $\pm 5\%$ of initial value (3) Q factor within $\pm 10\%$ of initial value ($\pm 20\%$ for 0402 & 0603 case sizes)	After 5 seconds at +260°C (with pre-conditioning)
Humidity	(1) No evidence of damage	After 500 hours at 60°C and 90 ~ 95% RH (0402 case size - after 96 hours 50°C and 90 ~ 95% RH)
Low Frequency Vibration	(2) Inductance change $\pm 5\%$ of initial value ($\pm 10\%$ for 0402 case size)	After 2 hrs per axis, 10 ~ 55Hz, 1.5mm amplitude
Thermal Shock	(3) Q factor within $\pm 10\%$ of initial value ($\pm 20\%$ for 0402 & 0603 case sizes)	After 100 cycles (10 cycles 0402) at -40°C and +125°C (30 minutes at each temperature)
Low Temperature Storage		After 500 hrs at -40°C
High Temperature Load Life	(1) No evidence of damage (2) Inductance change $\pm 10\%$ of initial value ($\pm 20\%$ for 0402 case size) (3) Q factor within $\pm 10\%$ of initial value ($\pm 20\%$ for 0402 & 0603 case sizes)	After 500 hrs at +125°C with rated DC current (0402 case size - after 1,000 hrs at +85°C)
Humidity Load Life	No evidence of short or open circuit	After 500 hrs at 60°C with 90 ~ 95% RH with rated DC current (0402 case size- 1,000 hrs at +40°C)

COMPONENT DIMENSIONS (mm):

Type	Case Size	A max.	B max.	C max.	D typ.	E typ.	F typ.
NIN-HK	0402	1.19	0.64	0.66	0.20	0.523	0.215
NIN-HJ	0603	1.80	1.12	1.02	0.38	0.76	0.33
NIN-HD	0805	2.29	1.68	1.55	0.51	1.27	0.50
NIN-HC	1008	2.92	2.79	2.29	0.51	2.00	0.50
NIN-HE	1206	3.56	2.16	1.52	.051	1.60	0.50
NIN-HA	1210	3.65	2.95	2.70	0.51	2.10	.050
NIN-HB	1812	4.95	3.81	3.43	1.78	2.90	.058

RECOMMEND LAND PATTERN DIMENSIONS (mm)

Type	H typ.	I typ.	J typ.
NIN-HK	0.65	0.35	0.50
NIN-HJ	1.02	0.64	0.64
NIN-HD	1.78	1.02	0.76
NIN-HC	2.54	1.02	1.27
NIN-HE	1.93	1.02	1.78
NIN-HA	3.02	1.02	1.78
NIN-HB	3.05	1.14	3.00



NIN-HK SERIES

K-SIZE (0402)

STANDARD VALUES

NIC P/N	INDUCTANCE VALUE (nH)	INDUCTANCE TOLERANCE	FREQUENCY (MHz)	Q FACTOR	SRF (MHz) Minimum	Rated DC Resistance (ohms)	Rated DC Current (mA)
NIN-HK1N8_TRF	1.8	S, J, K	250	20@250MHz	>6000	0.043	950
NIN-HK2N0_TRF	2.0	S, J, K	250	19@250MHz	7000	0.084	1040
NIN-HK2N2_TRF	2.2	S, J, K	250	22@250MHz	>6000	0.058	820
NIN-HK3N0_TRF	3.0	S, K	250	24@250MHz	>6000	0.063	790
NIN-HK3N3_TRF	3.3	S, J, K	250	24@250MHz	>6000	0.063	790
NIN-HK3N6_TRF	2.6	S, J, K	250	24@250MHz	>6000	0.063	790
NIN-HK3N9_TRF	3.9	S, J, K	250	24@250MHz	>6000	0.063	790
NIN-HK4N3_TRF	4.3	S, J, K	250	22@250MHz	>6000	0.070	750
NIN-HK4N7_TRF	4.7	S, J, K	250	20@250MHz	>6000	0.120	570
NIN-HK5N1_TRF	5.1	J, K	250	23@250MHz	>6000	0.100	620
NIN-HK5N6_TRF	5.6	J, K	250	25@250MHz	>6000	0.078	710
NIN-HK6N2_TRF	6.2	J, K	250	25@250MHz	>6000	0.078	710
NIN-HK6N8_TRF	6.8	J, K	250	24@250MHz	6000	0.105	610
NIN-HK7N5_TRF	7.5	G, J, K	250	25@250MHz	6000	0.120	570
NIN-HK8N2_TRF	8.2	G, J, K	250	25@250MHz	5500	0.110	590
NIN-HK9N1_TRF	9.1	G, J, K	250	25@250MHz	5500	0.110	590
NIN-HK100_TRF	10	G, J, K	250	24@250MHz	5500	0.150	510
NIN-HK110_TRF	11	G, J, K	250	26@250MHz	5500	0.120	570
NIN-HK120_TRF	12	G, J, K	250	26@250MHz	5500	0.120	570
NIN-HK130_TRF	13	G, J, K	250	24@250MHz	5000	0.180	460
NIN-HK150_TRF	15	G, J, K	250	24@250MHz	3300	0.204	560
NIN-HK160_TRF	16	G, J, K	250	25@250MHz	4500	0.280	370
NIN-HK200_TRF	20	G, J, K	250	26@250MHz	4000	0.240	400
NIN-HK220_TRF	22	G, J, K	250	24@250MHz	2800	0.360	400
NIN-HK240_TRF	24	G, J, K	250	25@250MHz	3500	0.360	330
NIN-HK270_TRF	27	G, J, K	250	25@250MHz	3500	0.380	320
NIN-HK300_TRF	30	G, J, K	250	25@250MHz	3300	0.380	320
NIN-HK330_TRF	33	G, J, K	250	24@250MHz	3200	0.550	260
NIN-HK360_TRF	36	G, J, K	250	25@250MHz	3100	0.600	250
NIN-HK390_TRF	39	G, J, K	250	25@250MHz	3000	0.600	250
NIN-HK430_TRF	43	G, J, K	250	25@250MHz	3000	0.680	240
NIN-HK470_TRF	47	G, J, K	250	25@250MHz	2900	0.950	200
NIN-HK510_TRF	51	G, J, K	250	25@250MHz	2850	0.950	200
NIN-HK560_TRF	56	G, J, K	250	25@250MHz	2800	1.050	190
NIN-HK620_TRF	62	G, J, K	250	25@250MHz	2600	1.050	190
NIN-HK680_TRF	68	G, J, K	250	25@250MHz	2500	1.350	170
NIN-HK750_TRF	75	G, J, K	250	24@250MHz	2400	1.750	140
NIN-HK820_TRF	82	G, J, K	250	25@250MHz	2300	1.900	140
NIN-HK910_TRF	91	G, J, K	250	25@250MHz	2100	1.950	140
NIN-HKR10_TRF	100	G, J, K	250	24@250MHz	1500	2.060	130
NIN-HKR12_TRF	120	G, J, K	250	25@250MHz	1000	2.060	130

Note: Extended values, tolerances, and enhanced versions are available please contact NIC for more details.



NIN-HJ SERIES

J-SIZE (0603)

STANDARD VALUES

NIC P/N	INDUCTANCE VALUE (nH)	INDUCTANCE TOLERANCE	FREQUENCY (MHz)	Q FACTOR	SRF (MHz) Minimum	Rated DC Resistance (ohms)	Rated DC Current (mA)
NIN-HJ1N6_TRF	1.6	S, K	250	22@250MHz	>6000	0.035	1150
NIN-HJ1N7_TRF	1.7	S, J,K	250	16@250MHz	>6000	0.043	1000
NIN-HJ1N8_TRF	1.8	S, J, K	250	18@250MHz	>6000	0.043	1000
NIN-HJ3N3_TRF	3.3	S, J,K	250	25@250MHz	>6000	0.059	850
NIN-HJ3N6_TRF	3.6	S, J, K	250	25@250MHz	>6000	0.059	850
NIN-HJ3N9_TRF	3.9	S, J, K	250	25@250MHz	>6000	0.059	850
NIN-HJ4N3_TRF	4.3	S, J, K	250	25@250MHz	>6000	0.059	850
NIN-HJ4N7_TRF	4.7	S, J, K	250	25@250MHz	>6000	0.065	800
NIN-HJ5N1_TRF	5.1	J, K	250	21@250MHz	>6000	0.13	600
NIN-HJ6N2_TRF	6.2	J, K	250	29@250MHz	>6000	0.095	700
NIN-HJ6N8_TRF	6.8	G, J, K	250	29@250MHz	>6000	0.095	700
NIN-HJ7N5_TRF	7.5	G, J, K	250	33@250MHz	>6000	0.095	700
NIN-HJ8N2_TRF	8.2	G, J, K	250	31@250MHz	>6000	0.095	700
NIN-HJ8N7_TRF	8.7	G, J, K	250	31@250MHz	>6000	0.095	700
NIN-HJ9N1_TRF	9.1	G, J, K	250	30@250MHz	6000	0.12	620
NIN-HJ9N5_TRF	9.5	G, J, K	250	26@250MHz	6000	0.16	540
NIN-HJ100_TRF	10	G, J, K	250	30@250MHz	6000	0.13	600
NIN-HJ110_TRF	11	G, J, K	250	35@250MHz	6000	0.13	600
NIN-HJ120_TRF	12	G, J, K	250	35@250MHz	6000	0.13	600
NIN-HJ130_TRF	13	G, J, K	250	35@250MHz	6000	0.13	600
NIN-HJ150_TRF	15	G, J, K	250	30@250MHz	4000	0.19	700
NIN-HJ160_TRF	16	G, J, K	250	37@250MHz	5500	0.15	550
NIN-HJ180_TRF	18	G, J, K	250	30@250MHz	3100	0.20	700
NIN-HJ200_TRF	20	G, J, K	250	37@250MHz	4900	0.15	550
NIN-HJ220_TRF	22	G, J, K	250	35@250MHz	3000	0.23	700
NIN-HJ230_TRF	23	G, J, K	250	40@250MHz	3800	0.19	490
NIN-HJ240_TRF	24	G, J, K	250	40@250MHz	3800	0.19	490
NIN-HJ250_TRF	25	G,J,K	250	40@250MHz	3700	0.19	490
NIN-HJ270_TRF	27	G, J, K	250	35@250MHz	2800	0.20	600
NIN-HJ300_TRF	30	G, J, K	250	38@250MHz	3300	0.21	470
NIN-HJ330_TRF	33	G, J, K	250	35@250MHz	2300	0.22	600
NIN-HJ360_TRF	36	G, J, K	250	40@250MHz	2900	0.22	460
NIN-HJ390_TRF	39	G, J, K	250	40@250MHz	2800	0.22	460
NIN-HJ430_TRF	43	G, J, K	250	40@250MHz	2700	0.27	400
NIN-HJ470_TRF	47	G, J, K	200	35@250MHz	2000	0.35	600
NIN-HJ510_TRF	51	G, J, K	200	35@250MHz	2400	0.3	390
NIN-HJ560_TRF	56	G, J, K	200	35@250MHz	1900	0.38	600
NIN-HJ620_TRF	62	G, J, K	200	36@250MHz	2300	0.38	350
NIN-HJ680_TRF	68	G, J, K	200	35@250MHz	1700	0.46	600
NIN-HJ720_TRF	72	G, J, K	150	34@250MHz	2100	0.43	320
NIN-HJ820_TRF	82	G, J, K	150	34@250MHz	1700	0.46	400
NIN-HJ910_TRF	91	G, J, K	150	34@250MHz	1900	0.52	300
NIN-HJR10_TRF	100	G, J, K	150	31@250MHz	1800	0.66	260
NIN-HJR11_TRF	110	G, J, K	150	32@250MHz	1700	0.73	250
NIN-HJR12_TRF	120	G, J, K	150	32@250MHz	1300	0.82	300
NIN-HJR15_TRF	150	G, J, K	150	28@150MHz	990	1.00	280

Note: Extended values, tolerances, and enhanced versions are available please contact NIC for more details.



NIN-HJ SERIES

J-SIZE (0603)

STANDARD VALUES

NIC P/N	INDUCTANCE VALUE (nH)	INDUCTANCE TOLERANCE	FREQUENCY (MHz)	Q FACTOR	SRF (MHz) Minimum	Rated DC Resistance (ohms)	Rated DC Current (mA)
NIN-HJR18_TRF	180	G, J, K	100	25@250MHz	1300	1.38	180
NIN-HJR20_TRF	200	G, J, K	100	25@250MHz	1250	1.9	150
NIN-HJR22_TRF	220	G, J, K	100	25@100MHz	990	2.00	200
NIN-HJR27_TRF	270	G, J, K	100	26@250MHz	960	3	120
NIN-HJR33_TRF	330	G, J, K	100	26@250MHz	800	4.2	100
NIN-HJR39_TRF	390	G, J, K	100	27@250MHz	800	4.5	100
NIN-HJR47_TRF	470	G, J, K	100	27@250MHz	700	5.7	90

Note: Extended values, tolerances, and enhanced versions are available please contact NIC for more details.

NIN-HD SERIES

D-SIZE (0805)

STANDARD VALUES

NIC P/N	INDUCTANCE VALUE (nH)	INDUCTANCE VALUE (nH)	FREQUENCY L/Q(MHz)	Q FACTOR	SRF (MHz) Minimum	Rated DC Resistance (ohms)	Rated DC Current (mA)
NIN-HD2N2_TRF	2.2	G, J, K	250/1500	40@1500MHz	>6000	0.1	600
NIN-HD3N3_TRF	3.3	G, J, K	250/1500	25@15-0MHz	>6000	0.2	600
NIN-HD6N8_TRF	6.8	G, J, K	250/1000	40@1000MHz	5000	0.11	600
NIN-HD8N2_TRF	8.2	G, J, K	250/1000	50@1000MHz	4700	0.19	600
NIN-HD100_TRF	10	G, J, K	250/500	50@500MHz	4200	0.14	600
NIN-HD120_TRF	12	G, J, K	250/500	40@500MHz	4000	0.15	600
NIN-HD150_TRF	15	G, J, K	250/500	40@500MHz	2900	0.17	600
NIN-HD180_TRF	18	G, J, K	250/500	50@500MHz	3300	0.2	600
NIN-HD220_TRF	22	G, J, K	250/500	55@500MHz	2000	0.22	500
NIN-HD270_TRF	27	G, J, K	250/500	55@500MHz	2500	0.25	500
NIN-HD330_TRF	33	G, J, K	250/500	60@500MHz	2050	0.27	500
NIN-HD390_TRF	39	G, J, K	250/500	60@500MHz	2000	0.29	500
NIN-HD470_TRF	47	G, J, K	200/500	50@500MHz	1600	0.31	500
NIN-HD560_TRF	56	G, J, K	200/500	55@500MHz	1550	0.32	500
NIN-HD680_TRF	68	G, J, K	200/500	55@500MHz	1450	0.38	500
NIN-HD820_TRF	82	G, J, K	150/500	60@500MHz	1300	0.42	400
NIN-HDR10_TRF	100	G, J, K	150/500	60@500MHz	1200	0.46	400
NIN-HDR12_TRF	120	G, J, K	150/250	50@250MHz	1100	0.51	400
NIN-HDR15_TRF	150	G, J, K	100/250	50@250MHz	920	0.56	400
NIN-HDR18_TRF	180	G, J, K	100/250	50@250MHz	870	0.64	400
NIN-HDR22_TRF	220	G, J, K	100/250	45@250MHz	850	0.7	400
NIN-HDR27_TRF	270	G, J, K	100/250	38@250MHz	650	1	350
NIN-HDR33_TRF	330	G, J, K	100/250	40@250MHz	600	1.4	310
NIN-HDR39_TRF	390	G, J, K	100/250	35@250MHz	560	1.5	290
NIN-HDR47_TRF	470	G, J, K	50/100	33@100MHz	375	1.72	250
NIN-HDR56_TRF	560	G, J, K	25/50	23@50MHz	340	1.9	230
NIN-HDR62_TRF	620	G, J, K	25/50	23@50MHz	280	1.95	200
NIN-HDR68_TRF	680	G, J, K	25/50	23@50MHz	270	2.05	190
NIN-HDR75_TRF	750	G, J, K	25/50	23@50MHz	240	2.1	180
NIN-HDR82_TRF	820	G, J, K	25/50	23@50MHz	250	2.3	180
NIN-HDR91_TRF	910	G, J, K	25/50	22@50MHz	230	2.4	160
NIN-HD1R0_TRF	1000	G, J, K	25/50	20@50MHz	200	2.5	150

Note: Extended values, tolerances, and enhanced versions are available please contact NIC for more details.



NIN-HA SERIES

D-SIZE (1210)

STANDARD VALUES

NIC P/N	INDUCTANCE VALUE (nH)	INDUCTANCE TOLERANCE	FREQUENCY L/Q(MHz)	Q FACTOR	SRF (MHz) Minimum	Rated DC Resistance (ohms)	Rated DC Current (mA)
NIN-HA3N9_TRF	3.9	G, J, K	100/300	30@300MHz	6000	0.05	1000
NIN-HA4N7_TRF	4.7	G, J, K	100/300	30@300MHz	5800	0.065	1000
NIN-HA8N2_TRF	8.2	G, J, K	100/300	30@300MHz	5500	0.07	1000
NIN-HA100_TRF	10	G, J, K	100/300	40@300MHz	4000	0.08	1000
NIN-HA120_TRF	12	G, J, K	100/300	40@300MHz	3200	0.08	1000
NIN-HA150_TRF	15	G, J, K	100/300	40@300MHz	3200	0.1	1000
NIN-HA180_TRF	18	G, J, K	100/300	50@300MHz	2800	0.1	1000
NIN-HA220_TRF	22	G, J, K	100/300	50@300MHz	2200	0.1	1000
NIN-HA270_TRF	27	G, J, K	100/300	50@300MHz	1800	0.11	1000
NIN-HA330_TRF	33	G, J, K	100/300	55@300MHz	1800	0.11	1000
NIN-HA390_TRF	39	G, J, K	100/300	55@300MHz	1500	0.12	1000
NIN-HA430_TRF	43	G, J, K	100/300	55@300MHz	1500	0.12	1000
NIN-HA470_TRF	47	G, J, K	100/300	55@300MHz	1500	0.13	1000
NIN-HA560_TRF	56	G, J, K	100/300	55@300MHz	1450	0.14	1000
NIN-HA680_TRF	68	G, J, K	100/300	55@300MHz	1200	0.15	900
NIN-HA820_TRF	82	G, J, K	100/300	55@300MHz	1000	0.2	900
NIN-HAR10_TRF	100	G, J, K	100/300	55@300MHz	900	0.2	850
NIN-HAR12_TRF	120	G, J, K	100/300	60@300MHz	800	0.25	800
NIN-HAR15_TRF	150	G, J, K	100/300	60@300MHz	700	0.25	750
NIN-HAR18_TRF	180	G, J, K	50/300	60@300MHz	650	0.3	700
NIN-HAR22_TRF	220	G, J, K	50/300	60@300MHz	650	0.4	770
NIN-HAR27_TRF	270	G, J, K	50/300	40@300MHz	580	0.4	630
NIN-HAR33_TRF	330	G, J, K	50/150	45@150MHz	580	0.58	590
NIN-HAR39_TRF	390	G, J, K	50/150	45@150MHz	510	0.58	530
NIN-HAR47_TRF	470	G, J, K	50/150	45@150MHz	480	0.8	490
NIN-HAR56_TRF	560	G, J, K	35/150	45@150MHz	420	1.1	460
NIN-HAR68_TRF	680	G, J, K	35/150	45@150MHz	400	1.2	430
NIN-HAR82_TRF	820	G, J, K	35/150	45@150MHz	370	1.82	400
NIN-HA1R0_TRF	1000	G, J, K	35/150	45@150MHz	340	1.85	320
NIN-HA1R2_TRF	1200	G, J, K	35/150	35@150MHz	220	1.87	300
NIN-HA1R5_TRF	1500	G, J, K	7.9/50	20@50MHz	160	1.95	310
NIN-HA1R8_TRF	1800	G, J, K	7.9/50	30@50MHz	160	2.25	310
NIN-HA2R2_TRF	2200	G, J, K	7.9/50	25@50MHz	130	2.41	310
NIN-HA2R7_TRF	2700	G, J, K	7.9/50	25@50MHz	110	2.85	300
NIN-HA3R0_TRF	3000	G, J, K	7.9/25	20@25MHz	110	3.12	300
NIN-HA3R9_TRF	3900	G, J, K	7.9/25	20@25MHz	60	3.6	290
NIN-HA4R7_TRF	4700	G, J, K	7.9/25	20@25MHz	60	4	280
NIN-HA5R6_TRF	5600	G, J, K	7.9/25	15@25MHz	50	5	250
NIN-HA6R8_TRF	6800	G, J, K	7.9	15@7.9MHz	40	8	230
NIN-HA8R6_TRF	8600	G, J, K	7.9	15@7.9MHz	40	9	200

Note: Extended values, tolerances, and enhanced versions are available please contact NIC for more details.



