

HUBER+SUHNER® DATA SHEET

Within Series Adaptor: 34_TNC-50-0-1/133_N



Description

Bulkhead adaptor jack/jack
 TNC jack (female) / TNC jack (female)
 Interface standard
 Series TNC - IEC 60169-17_MIL-STD-348A/313_CECC 22200



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	11 GHz		
Frequency range	DC to 2 GHz	2 to 8 GHz	8 to 11 GHz
Return loss	≥ 26 dB	≥ 14 dB	≥ 10 dB

Mechanical Data

Number of matings	500
Weight	0.0195 kg

Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts

Interface - TNC jack (female)

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	VMQ (Silicone rubber)

Surface Plating

Gold Plating (Nickel underplated)
 SUCOPLATE (R) Plating
 SUCOPLATE (R) Plating

Interface - TNC jack (female)

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	VMQ (Silicone rubber)

Gold Plating (Nickel underplated)
 SUCOPLATE (R) Plating
 SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00013573
Mounting hole	DOU-00008751

Ordering Information

Single package	34_TNC-50-0-1/133_NE
----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!
 It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions