

Within Series Adaptor 31_BNC-50-0-1/133_N

Description

Adaptor jack/jack
BNC jack (female) / BNC jack (female)

Interface standard
Series BNC - IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

| | |
|--------------------------|-------------------------------------|
| Impedance | 50 Ω |
| Interface frequency max. | 4 GHz |
| VSWR | DC - 4 GHz ≤ 1.06 + 0.04 f (GHz) |

Mechanical Data

| | |
|-------------------|-----------|
| Number of matings | 500 |
| Weight | 0.0123 kg |

Environmental Data

| | |
|--|-------------------------------|
| Operating temperature 2011/65/EU (RoHS) | -65 °C to 165 °C compliant |
|--|-------------------------------|

Material Data

Interface - BNC jack (female)

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Interface - BNC jack (female)

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|-------------------|--------------|
| Catalogue drawing | DCA-00013802 |
|-------------------|--------------|

Ordering Information

| | |
|----------------|----------------------|
| Single package | 31_BNC-50-0-1/133_NE |
|----------------|----------------------|