

## 1. General description

Lubricant and assembly paste for stainless steel connections. Prevents fit- and fretting corrosion.

## 2. Features

- Enables easy disassembly of threaded parts, gaskets and flanges, even after a long time of to high pressure and high temperature.
- Protects against burning-in, corrosion and seizing.
- Stops and prevents disc brake noise and vibration.
- None chlorinated solvents.
- Totally free of lead and chromates.
- Excellent water resistance.
- Functional over a wide temperature range.

## 3. Applications

- Flange connections under high temperature conditions.
- Pin or spline connections.
- Threaded connections.

## 4. Directions

- Apply to a clean, dry surface.
- Apply a thin even film.
- Do not mix with other products.
- Do not use on energized equipment.
- Use only with adequate ventilation.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**


## 5. Typical product data (without propellant)

Appearance	Aerosol	Bulk
Color	Paste.	Paste.
	Off-white.	White.



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
**www.crcind.com**





# Technical data sheet CERAMIC PASTE

Reference : 32351

Odor	Solvent.	Perceptible odour.
Flash Point	< 0 °C (Closed Cup)	>200 °C
Density	0.857 g/cm <sup>3</sup> (@ 20°C).	1.419 g/cm <sup>3</sup> (@ 20°C).
Operating temperature active product	-40 -->+1400 °C	-40-->+1400 °C
4-ball weld load active product	3800 N	3800 N
NLGI class	3	3

## 6. Packaging

Aerosol 12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC\_GREEN-CERAMIC\_PASTE-20130827

Date



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

